

NOTICE INVITING TENDER (NIT)

SUPPLY

OF

SINGLE PHASE NATURAL ORGANIC ESTER OIL FILLED COMPLETELY SELF PROTECTED (CSP) TRANSFORMER OF RATING 25KVA 6.35/0.240kV

NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]

Due Date for Submission: 28.06.2024, 14:00 HRS

BSES YAMUNA POWER LIMITED (BYPL)
CONTRACTS & MATERIALS DEPT.,
SHAKTI KIRAN BUILDING, KARKARDOOMA,
DELHI-110032
CIN: U40109DL2001PLC111525


WEBSITE: www.bsesdelhi.com

This document is a property of BYPL. This document is meant for the exclusive purpose of bidding against this NIT Number/Specification and shall not be transferred, reproduced, or otherwise used for purposes other than that for which it is specifically issued.



NIT INDEX

S No.	DOCUMENT DESCRIPTION	PAGE NO		
VOLUME – I				
1	INFORMATION TO BIDDER (ITB)	1 To 17		
1.00	APPENDIX I			
1.01	BID INDEX FOR PART-A (TECHNICAL BID)			
1.02	BID FORM			
1.03	TENDER FEE DETAILS			
1.04	EMD DETAILS			
1.05	FORMAT FOR EMD BANK GUARANTEE			
1.06	COMMUNICATION DETAILS OF THE BIDDER			
1.07	MANUFACTURER AUTHORIZATION FORM			
1.08	QUALIFYING CRITERIA COMPLIANCE INDEX - TECHNICAL CRITERIA			
1.09	LIST OF PURCHASE ORDERS EXECUTED & DELIVERY DETAILS IN SUPPORT OF QUALIFYING REQUIREMENT			
1.10	LIST OF PERFORMANCE CERTIFICATES IN SUPPORT OF QUALIFYING REQUIREMENT			
1.11	SCHEDULE OF DEVIATIONS - TECHNICAL	_		
1.12	TYPE TEST REPORTS (SEQUENCE OF TESTS SHALL BE STRICTLY IN ACCORDANCE WITH RELEVANT IS/IEC)			
1.13	SAMPLE SUBMISSION DETAILS (IF APPLICABLE AS PER SPECIFICATION)	_		
1.14	QUALIFYING CRITERIA COMPLIANCE INDEX - COMMERCIAL CRITERIA			
1.15	UNDERTAKINGS			
1.16	SCHEDULE OF DEVIATIONS - COMMERCIAL	_		
1.17	ACCEPTANCE FORM FOR PARTICIPATION IN REVERSE AUCTION EVENT	_		
1.18	VENDOR CODE OF CONDUCT			
2	GENERAL CONDITION OF CONTRACT - SUPPLY	1 To 17		
2.00	APPENDIX II			
2.01	FORMAT FOR PERFORMANCE BANK GUARANTEE			
2.02	BENEFICIARY'S BANK DETAILS WITH IFSC CODE	1 To 6		
2.03	FORMAT OF WARRANTY/GUARANTEE CERTIFICATE			
2.04	FORMAT OF UNDERTAKING GST			
2.05	SUMMARY OF COMMERCIAL TERMS AND CONDITIONS			
VOLUME – II - PRICE BID FORMAT 1 To 2				
VOLUME	- III - TECHNICAL SPECIFICATIONS	1 To 36		



INFORMATION TO BIDDER (ITB)
NIT NO: CMC/BY/24-25/RS/SkS/SV/09
[RFx Number: 2200000026]

Page **1** of **17**

Bidders seal & Signature

SECTION – I: REQUEST FOR QUOTATION

1.00 EVENT INFORMATION

1.01 BSES Yamuna Power Ltd (hereinafter referred to as **"BYPL"**) invites **Open Tender** in the E-Tender Bidding Process on a "Single Stage: Two Parts" from interested Bidders as detailed below:

Tender Description	Tender Fee (₹)	Estimated Cost (₹)	EMD Amount (₹)	Delivery at
SUPPLY OF SINGLE PHASE NATURAL ORGANIC ESTER OIL FILLED COMPLETELY SELF PROTECTED (CSP) TRANSFORMER OF RATING 25KVA 6.35/0.240kV	1,180	5.88 Crore	5.88 Lakh	Delhi Store(s)/ Site(s)

The bidder must qualify the requirements as specified in clause 2.0 stated below.

- 1.02 The tender document is available for downloading from our website www.bsesdelhi.com --> BSES YAMUNA POWER LTD --> Tender --> Open Tenders or through our E-Tendering portal link (https://srmprdportal.bsesdelhi.com:50001/irj/portal).
- 1.03 **Tender Fee**: The bidder has to compulsorily submit the non-refundable tender fee of ₹ 1,180/- as demand draft or online transfer of the requisite amount through IMPS/NEFT/RTGS covering the cost of bid documents. Any such bid submitted without this Fee shall be rejected.
- 1.04 **Earnest Money Deposit (EMD)** of ₹ 5,88,000/- (Five Lakhs and Eighty Eight Thousand only) valid for 120 days from the due date of bid submission in the form of BG/FD/online transfer of the requisite amount through IMPS/NEFT/RTGS. Any such bid submitted without EMD shall be rejected.

1.05 TIME SCHEDULE

The bidders should complete the following events within the dates specified as under:

S. No.	Events	Due date & Time
1	Date of availability of tender documents from BYPL Website &	up to 28.06.2024,
	SRM	14:00 Hours
2	Date & Time of Pre-Bid Meeting Pre-Bid Meeting will be done online, Register in advance for this meeting via, the Zoom Meeting link: https://zoom.us/meeting/register/tJYpduurrzMiHNeOeDUDbZDJLk7ztRVoVOu4 After registering, you will receive a confirmation email containing information about joining the meeting.	21.06.2024, 11:00 Hours
3	Last Date of receipt of pre-bid queries, if any (Queries to be submitted via e-mail)	21.06.2024 up to 18:00 Hours
4	Last Date of replies to all the pre-bid queries as received	24.06.2024 up to 17:00 Hours
5	Last date and time of receipt of Complete Bids (Tender Fees, EMD, Part A & Part B)	28.06.2024, 14:00HRS
6	Date & Time of Opening of PART A – EMD and Technical Bid	28.06.2024, 15:00HRS
7	Date & Time of opening of Price/RA of qualified bids	Will be notified to the qualified bidders through our website/e-mail

INFORMATION TO BIDDER (ITB)	Page 2 of 17	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		

Note: In the event of the last date specified for submission of bids and the date of opening of bids is declared as a closed holiday for the BSES office, the last date of submission of bids and date of opening of bids will be the following working day at the appointed times.

1.06 The Bid shall be submitted online in two (02) parts. Details of the parts are as follows:

Part A – Techno Commercial Bid

Part B – Price Bid

Bids will be submitted online and received up to **28.06.2024**, **14:00 Hr.** at the address given below.

Part A of the Bid shall be opened online on 28.06.2024, 15:00 Hr.

Part B of the Bid will be opened in case of Techno-Commercially Qualified Bidders and the date of opening of same shall be intimated in due course. It is the sole responsibility of the bidder to ensure that the bid documents are submitted online and reach this office on or before the last date.

Head of Department
Contracts & Materials Deptt.
BSES Yamuna Power Ltd
Reception, Ground Floor
Shaktikiran Building, Karkardooma
Delhi 110032

All envelopes shall be duly superscribed "BID FOR SUPPLY OF SINGLE PHASE NATURAL ORGANIC ESTER OIL FILLED COMPLETELY SELF PROTECTED (CSP) TRANSFORMER OF RATING 25KVA 6.35/0.240kV" "NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026] DUE ON 28.06.2024, 14:00 Hr."

- 1.07 BSES Yamuna Power Ltd reserves the right to accept/reject any or all tenders without assigning any reason thereof in the event of the following:
 - a) Tender is received after the due date and time.
 - b) Tender fee of requisite value is not submitted.
 - c) Earnest Money Deposit (EMD) of requisite value & validity is not submitted in the shape of a Bank Guarantee drawn in favour of BSES Yamuna Power Ltd, payable at Delhi or Online transfer of requisite amount through IMPS/NEFT/RTGS.
 - d) Price Bid as per the Price Schedule is not submitted.
 - e) Incomplete Bids.
 - f) Necessary documents against compliance to Qualification Requirements mentioned in Section 1 Clause 2.0 of this Tender Document.
 - g) Complete documents/details are not enclosed as per the Bid Index for Part-A (Technical Bid) at APPENDIX I ANNEXURE 1.01.
 - h) Filled in Schedule of Deviations as per Annexure is not submitted.

2.00 QUALIFICATION CRITERIA

The prospective bidder must qualify for all of the following requirements and shall be eligible to participate in the bidding who meets the following requirements and management has a right to disqualify those bidders who do not meet these requirements.

2.01 Technical Criteria:

S. No.	Criteria	Documents to be submitted by the bidder
1	The bidder should have own manufacturing facility in India for Distribution transformer of similar rating or higher since last 3 years.	i. Manufacturing and factory incorporation certificate / Undertaking

INFORMATION TO BIDDER (ITB)	Page 3 of 17	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		

		ii. The details of manufacturing units, locations and works from where supply against this tender shall be proposed to be furnished.
2	The Bidder should have supplied at least 500 Nos of transformers of similar rating or higher in last 5 years from the date of bid opening to any utilities/SEBs/PSUs/ reputed company wherein the end user shall be utilities/SEBs/PSUs.	i. Summary list of executed Purchase orders (Details to be submitted as per the format enclosed in APPENDIX I - ANNEXURE – 1.09) ii. Purchase order copies iii. Material delivery clearance certificate copy or Invoice Copies or Delivery completion/ Performance certificate
3	Performance certificate for minimum 2 year satisfactory performance for similar rating or higher rating supplied in last 7 years from the date of bid opening from at least two utilities/SEBs/PSUs/reputed company wherein the end user shall be utilities/ SEBs/PSUs. In case of bidder has a previous association with BRPL/BYPL for similar product and service, the performance feedback for that bidder by BRPL/BYPL shall only be considered irrespective of performance certificate issued by any third organization.	Performance Certificates (Details to be submitted as per the format enclosed in APPENDIX I - ANNEXURE – 1.10)
4	The bidder should have plant installed capacity to supply of 200 nos of transformer per month for similar or higher rating.	Installed Manufacturing Capacity (duly certified by the CE/CA/DIC/Self-Undertaking/Government Organization/others)
5	The bidder must possess a valid ISO 9001:2015 certification.	Valid copy of Certification
6	The bidder should have servicing, repairing, testing & refurbishment facility in INDIA with necessary spares and testing equipments for providing prompt after sales service for Distribution Transformer.	Relevant Details/certificates/Undertaking (Details of the set-up available shall be brought out in the offer. the bidder shall also submit undertaking along with the bid confirming the infrastructure details submitted)

2.02 Commercial Criteria:

COIIII	Hercial Criteria:	
S. No.	Criteria	Documents to be submitted by the bidder
7	Bidder should have an Average Annual Sales Turnover of Rs 6 Crores or more in the last three (3) Financial Years (i.e., FY 2020-21, 2021-22 & 2022-23).	Balance Sheet / Copy of audited P&L Account / Duly certified CA certificate having UDIN to be submitted (Details to be submitted as per the format enclosed in APPENDIX I - ANNEXURE – 1.14)
8	The Bidder shall submit an undertaking that "No Litigation" is pending with the BYPL or its Group/Associates Companies as on the date of bid opening.	Self-Undertaking (as per the format enclosed in APPENDIX I - ANNEXURE – 1.15)

INFORMATION TO BIDDER (ITB)	Page 4 of 17	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		

		(Details to be submitted as per the format enclosed in APPENDIX I - ANNEXURE – 1.14)
9	An undertaking (self-certificate) that the bidder has not been blacklisted/debarred by any central/state government institution/Electricity utilities as on the date of bid opening.	Self-Undertaking (as per the format enclosed in APPENDIX I - ANNEXURE – 1.15) (Details to be submitted as per the format enclosed in APPENDIX I - ANNEXURE – 1.14)
10	The bidder must have a valid PAN No. and GST Registration Number, in addition to other statutory compliances. The bidder must submit a copy of registrations and submit an undertaking that the bidder shall comply with all the statuary compliances as per the laws/rules etc. before the start of the supply/work.	Relevant Statutory Documents Copy/ Self Undertaking (as per the format enclosed in APPENDIX I - ANNEXURE – 1.15) (Details to be submitted as per the format enclosed in APPENDIX I - ANNEXURE – 1.14)

The subsidiaries of global/Indian companies are also eligible to bid if the qualification requirements stated above are met independently or in combination with parent/sister concern/group Company. However, the bidder should have an establishment of permanent nature in India.

Notwithstanding anything stated above, BYPL reserves the right to assess the bidder's capability to perform the contract, assess the capability and installed capacity of the Bidder for carrying out the supplies, should the circumstances warrant such assessment in the overall interest of the purchaser. In this regard the decision of the purchaser is final.

3.00 BIDDING AND AWARD PROCESS

Bidders are requested to submit their offer strictly in line with this tender document. Normally, the deviations to tender terms are not admissible and the bids with deviations are liable for rejection. Hence, the bidders are advised to refrain from taking any deviations on this Tender. Still, in case of any deviations, all such deviations shall be set out by the Bidders, clause by clause in the "Annexure - Schedule of Deviations" and the same shall be submitted as a part of the Technical Bid.

3.01 **BID SUBMISSION**

BIDS ARE INVITED THROUGH THE E-PROCUREMENT PORTAL:

BSES will carry out E-Procurement through its e-procurement portal (https://srmprdportal.bsesdelhi.com:50001/irj/portal).

Interested Non-registered bidders are requested to obtain the portal user name and password (if not available) for bid submission. For participating in e-Tenders of BYPL, please write a mail to

- 1. Mr Rakesh Sharma, E-mail: Rakesh.Ku.Sharma@relianceada.com,
- 2. Mr Sumit Verma, E-mail: sumit.ra.verma@@relianceada.com, with your details as per below:
- a) Existing Vendor Code with BYPL or its Group/Associates Companies (if available):
- b) Trade Name:
- c) Address of Principal Place of Business:
- d) Contact Person's Name:
- e) Contact Person's Designation:
- f) Contact Person's Mobile No.:

INFORMATION TO BIDDER (ITB) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 5 of 17	Bidders seal & Signature
--	----------------------------	--------------------------

- g) Contact Person's email ID:
- h) Also, attach a valid copy of the Power of Attorney in favour of the above-mentioned Contact Person for being authorized to receive user ID and password on behalf of their organization.

The login ID details shall be sent through email to the email ID mentioned by you for the same.

Bids shall be submitted in 2 (Two) parts on the assigned folder of the e-procurement site. Please refer to the user manual available at https://srmprdportal.bsesdelhi.com:50001/irj/portal and enclosed with the tender.

Bids have to be mandatorily submitted only through the e-procurement portal of BSES Delhi. Bids submitted through any other form/ route shall not be admissible.

However, documents that necessarily have to be submitted in originals like Tender Fee (in the form of DD) or EMD (in the form of BG/FD/DD as applicable) and any other documents mentioned in the tender documents have to be submitted at the BYPL office before the due date & time of submission.

Please mention our NIT Number: - on the Tender and drop the same in our Tender Box placed at BSES Yamuna Power Ltd, Reception, Ground Floor, Shaktikiran Building, Karkardooma, Delhi 110032

The bids and the outer envelope shall be addressed to the following:

Head of Department

Contracts & Materials Deptt.

BSES Yamuna Power Ltd, Shaktikiran Building, Karkardooma, Delhi 110032 Kindly Note:

- > The bidder has to ensure that the tender is dropped in the correct box designated for tender submission only.
- > BYPL shall not be responsible for any wrong placement of tender documents by the bidder.

This is a two-part bid process. Bidders are to submit the bids online in 2(Two) parts **PART-A TECHNICAL BID & COMMERCIAL TERMS & CONDITIONS** and **Part-B FINANCIAL BID** and shall be submitted before the due date & time specified.

PART A:: TECHNICAL BID comprising of the following, do not contain any cost information whatsoever and shall be submitted within the due date:

S. No.	Descriptions	Type of Documents/Format	
A.1	Bid Details		
1	Bid Index for Part-A	In the prescribed format enclosed at APPENDIX I	
	(Technical Bid)	ANNEXURE – 1.01	
2	Cover Letter, if any	Standard Format	
3	Bid Form (Unpriced)	Duly Signed Bid Form as per enclosed format at	
	Duly Signed	APPENDIX I ANNEXURE – 1.02	
4	Tender Fee	Non-refundable demand draft or online transfer of the requisite amount through IMPS/NEFT/RTGS for Rs 1,180/-, Duly filled and signed as per enclosed format at APPENDIX I ANNEXURE – 1.03	
5	EMD	Online transfer of the requisite amount through IMPS/NEFT/RTGS or FD or BG in the prescribed stamp paper & format enclosed at APPENDIX I ANNEXURE –	

INFORMATION TO BIDDER (ITB)	Page 6 of 17	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09	_	
[RFx Number: 2200000026]		

		1.05, EMD Details Duly filled and signed as per enclosed format at APPENDIX I ANNEXURE – 1.04		
6	Power-of-Attorney/ Authorization Letter	In the standard stamp paper/letter		
A.2	Technical Bid			
7	Communication Details of the Bidder	Duly filled and signed as per enclosed format at APPENDIX I ANNEXURE – 1.06		
8	Manufacturer Authorization Form (as	Duly filled and signed as per enclosed format at APPENDIX I ANNEXURE – 1.07		
	applicable)	7 THE ENGLY THE PROPERTY OF TH		
9	Technical Qualifying	Documentary evidence in support of qualifying criteria		
	Criteria Compliance	mentioned in Section 1 Clause 2.00. Duly filled and signed		
	Index & Documents	as per enclosed format at APPENDIX I ANNEXURE – 1.08, ANNEXURE – 1.09 & ANNEXURE – 1.10		
10	Schedule of Deviations	Duly filled and signed as per enclosed format at		
10	- Technical	APPENDIX I ANNEXURE – 1.11		
11	Technical Details/	Bidder shall submit duly filled GTP with all Technical		
	Filled in Guaranteed	documents		
	Technical particulars			
	(GTP) as per			
	specification			
12	Technical Drawings as	Bidder shall submit all Drawings as per the specification		
	per specification			
13	Type Test Reports	Bidders shall submit a copy of type test reports in their		
		technical bids in support of technical specifications. Duly		
		filled and signed as per enclosed format at APPENDIX I ANNEXURE -1.12		
14	Sample Submission	Duly filled and signed as per enclosed format at		
	Details (if applicable	APPENDIX I ANNEXURE – 1.13		
	as per specification)			
15	Product Catalogue (If	Bidders shall submit a copy of the product catalogue in		
	applicable)	their technical bids in support of technical specifications		
16	Manufacturer's Quality	Bidders shall submit a copy of MQP in their technical bids		
17	Assurance Plan Other drawings/	in support of technical specifications		
11	documents mentioned	Bidders shall submit a copy of documents in their technical bids in support of technical specifications		
	in technical	recurrical blus in support of technical specifications		
	specification			
18	Testing Facilities	Bidder shall submit the details of testing facilities		
-		available at their works/factory.		
A.3	Commercial Bid			
19	Company Profile,	Bidder shall submit the details of Organization &		
	Organization Chart &	Manpower with qualification and experience.		
	Manpower Details.			
20	Commercial Qualifying	Documentary evidence in support of qualifying criteria		
	Criteria Compliance	mentioned in Section 1 Clause 2.00. Duly filled and signed		
	Index & Documents	as per enclosed format at APPENDIX I ANNEXURE – 1.14		
21	Undertakings	Duly signed self-undertakings as per enclosed format at APPENDIX I ANNEXURE – 1.15		
22	Schedule of Deviations	, ,		
	- Commercial	APPENDIX I ANNEXURE – 1.16		

INFORMATION TO BIDDER (ITB) NIT NO: CMC/BY/24-25/RS/SkS/SV/09	Page 7 of 17	Bidders seal & Signature
[RFx Number: 2200000026]		

23	Acceptance Form For	Duly signed Acceptance Form For Participation In		
	Participation in	Reverse Auction Event as per enclosed format at		
	Reverse Auction Event	APPENDIX I ANNEXURE – 1.17		
24	4 Commercial Terms and Acceptance of Commercial Terms and			
	Conditions	Delivery Schedule/Period, Payment terms, PBG etc. Duly		
		filled and signed as per enclosed format at APPENDIX II		
		ANNEXURE – 2.05		
25	Un price Bid Duly	Item wise marked as "Quoted" & Duly Signed Un price		
	Signed	Bid as per enclosed format at VOLUME – II - PRICE BID		
		FORMAT		
26	Signed Tender	Original Tender documents duly stamped & signed on		
	document	each page as a token of acceptance		

PART B:: FINANCIAL BID comprising of

- Price strictly in the Format enclosed at VOLUME II PRICE BID FORMAT indicating Break up of basic price, taxes & duties, etc.
- The Bidder has to submit the item-wise price bifurcation in the bid. An unpriced copy must be attached with the Part A (Technical Bid).

This will be opened internally after techno-commercial evaluation and only of the qualified bidders.

REVERSE AUCTION CLAUSE:: Purchaser reserves the right to use the reverse auction as an optional tool through SAP-SRM as an integral part of the entire tendering process. All technocommercially qualified bidders shall participate in the reverse auction. Reverse Auction will be carried out on individual item-wise rates or Package-wise.

Notwithstanding anything stated above, the Purchaser reserves the right to assess the bidder's capability to perform the contract, should the circumstances warrant such assessment in the overall interest of the purchaser. In this regard the decision of the purchaser is final. Bidder is to submit their acceptance as per the format APPENDIX I ANNEXURE -1.17.

BIDS RECEIVED AFTER THE DUE DATE AND TIME MAY BE LIABLE FOR REJECTION

4.00 AWARD DECISION

- 4.01 Purchaser intends to award the business on the lowest bid basis, so suppliers are encouraged to submit the bid competitively. The decision to place a Rate Contract/Purchase Order/LOI solely depends on the purchaser on the cost competitiveness across multiple lots, quality, delivery and bidder's capacity, in addition to other factors that Purchaser may deem relevant.
- 4.02 In the event of your bid being selected by the purchaser (and/or its affiliates) and you subsequent DEFAULT on your bid; you will be required to pay the purchaser (and/or its affiliates) an amount equal to the difference in your bid and the next lowest bid on the quantity declared in NIT/RFO.
- 4.03 In case any supplier is found unsatisfactory during the delivery process, the award may be cancelled and BYPL reserves the right to award other suppliers who are found fit.
- 4.04 Rate shall remain FIRM till the validity of the Contract.
- 4.05 Quantity Variation: The purchaser reserves the right to vary the quantity by (±) 30% of the tender quantity during the execution of the rate contract.

- 4.06 Quantity Splitting: The purchaser reserves the right to distribute the procurable quantity on one or more than one of the eligible tenders. If the quantity is to be split, quantity distribution shall be in the manner detailed below:
 - a) If the quantity is split among 2 bidders, it will be done at 70:30 on the L1 price.
 - b) If the quantity is split among 3 bidders, it will be done at 50:30:20 on the L1 price.

Note: If quantity needs to be distributed and order splitting is required, quantity distribution shall be maximum among three (3) bidders.

5.00 MARKET INTEGRITY

We have a fair and competitive marketplace. The rules for bidders are outlined in the Terms & Conditions. Bidders must agree to these rules before participating. In addition to other remedies available, we reserve the right to exclude a bidder from participating in future markets due to the bidder's violation of any of the rules or obligations contained in the Terms & Conditions. Bidders who violate the marketplace rules or engage in behaviour that disrupts the fair execution of the marketplace restrict a bidder to the length of time, depending upon the seriousness of the violation. Examples of violations include, but are not limited to:

- Failure to honour prices submitted to the marketplace.
- Breach of the terms of the published in Request for Quotation/NIT.

6.00 SUPPLIER CONFIDENTIALITY

All information contained in this RFQ is confidential and shall not be disclosed, published or advertised in any manner without written authorization from BYPL. This includes all bidding information submitted.

All RFQ documents remain the property of BYPL and all suppliers are required to return these documents to BYPL upon request.

Suppliers who do not honour these confidentiality provisions will be excluded from participating in future bidding events.

7.00 CONTACT INFORMATION

Technical clarification, if any, as regards this RFQ shall be sought in writing and sent by e-mail/post/courier to the following addresses. The same shall not be communicated through phone

Address	Name/ Designation	E-mail Address
	Technical	
CES Dept. 3 rd Floor, B-Block,	Jeena Borana DGM (CES)	jeena.borana@relianceada.com
BSES Yamuna Power Ltd Shaktikiran Building,	Srinivas Gopu GM (CES)	srinivas.gopu@relianceada.com
Karkardooma, Delhi 110032	Gaurav Sharma Addl. VP (HOD-CES)	gaurav.a.sharma@relianceada.com
	Commercial	
Co.M Dont 2rd Floor A Plack	Sumit Verma GM (C&M)	sumit.ra.verma@relianceada.com
C&M Dept. 3 rd Floor, A-Block, BSES Yamuna Power Ltd Shaktikiran Building,	Santosh Singh Addl. VP (Head- Procurement)	santosh.kum.singh@relianceada.com
Karkardooma, Delhi 110032	Robin Sebastian VP (HOD-C&M)	robin.sebastian@relianceada.com

Page 9 of 17	Bidders seal & Signature
	Page 9 of 17

SECTION – II: INSTRUCTION TO BIDDERS

A. GENERAL

1.00 BSES Yamuna Power Ltd, hereinafter referred to as "The Purchaser" is desirous of implementing the various Systems Improvement/Repair & Maintenance works at their respective licensed area in Delhi The Purchaser has now floated this tender for procurement of material notified earlier in this bid document.

2.00 SCOPE OF WORK

The scope shall include Design, Manufacture, testing at works conforming to the Technical Specifications/IS along with Packing, Forwarding, Transportation Unloading and proper stacking at Purchaser's stores/site.

3.0 DISCLAIMER

- 3.01 This Document includes statements, which reflect various assumptions, which may or may not be correct. Each Bidder/Bidding Consortium should conduct its estimation and analysis and should check the accuracy, reliability and completeness of the information in this Document and obtain independent advice from appropriate sources in their interest.
- 3.02 Neither Purchaser nor its employees will have any liability whatsoever to any Bidder or any other person under the law or contract, the principles of restitution or unjust enrichment or otherwise for any loss, expense or damage whatsoever which may arise from or be incurred or suffered in connection with anything contained in this document, any matter deemed to form part of this Document, provision of Services and any other information supplied by or on behalf of Purchaser or its employees, or otherwise a rising in any way from the selection process for the Supply.
- 3.03 Though adequate care has been taken while issuing the Bid document, the Bidder should satisfy itself that the Documents are complete in all respects. Intimation of any discrepancy shall be given to this office immediately.
- 3.04 This Document and the information contained herein are Strictly Confidential and are for the use of only the person(s) to whom it is issued. It may not be copied or distributed by the recipient to third parties (other than in confidence to the recipient's professional advisors).

4 COST OF BIDDING

The Bidder shall bear all costs associated with the preparation and submission of its Bid and the Purchaser will in no case be responsible or liable for those costs.

B. BIDDING DOCUMENTS

- 5.01 The Scope of Work, Bidding Procedures and Contract Terms are described in the Bidding Documents.
- 5.02 The Bidder is expected to examine the Bidding Documents, including all Instructions, Forms, Terms and Specifications. Failure to furnish all information required by the Bidding Documents or submission of a Bid not substantially responsive to the Bidding Documents in every respect may result in the rejection of the Bid.

INFORMATION TO BIDDER (ITB) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 10 of 17	Bidders seal & Signature
--	-----------------------------	--------------------------

6.0 **AMENDMENT OF BIDDING DOCUMENTS**

- 6.01 At any time before the deadline for submission of Bids, the Purchaser may for any reason, whether at its initiative or in response to a clarification requested by a prospective Bidder, modify the Bidding Documents by Amendment.
- 6.02 The Amendment shall be part of the Bidding Documents, pursuant to Clause 5.01, and it will be notified on the website www.bsesdelhi.com and the same will be binding on them.
- 6.03 To afford prospective Bidders reasonable time in which to take the Amendment into account in preparing their Bids, the Purchaser may, at its discretion, extend the deadline for the submission of Bids. The same shall be published as a corrigendum on the website www.bsesdelhi.com
- 6.04 Purchaser shall reserve the rights to the following:
 - a) Extend the due date of submission,
 - b) Modify the tender document in part/whole,
 - c) Cancel the entire tender
- 6.05 Bidders are requested to visit the website regularly for any modification/clarification/corrigendum/addendum of the bid documents.

C. PREPARATION OF BIDS

7.0 LANGUAGE OF BID

The Bid prepared by the Bidder, and all correspondence and documents relating to the Bid exchanged by the Bidder and the Purchaser, shall be written in the English Language. Any printed literature furnished by the Bidder may be written in another language, provided that this literature is accompanied by an English translation, in which case, for purposes of interpretation of the Bid, the English translation shall govern.

8.0 **DOCUMENTS COMPRISING THE BID**

The Bid prepared and submitted by the Bidder shall comprise the following components:

- (a) All the Bids must be accompanied by the required Tender Fees and EMD as mentioned in the tender.
- (b) PART A Technical Bid and
- (c) PART B Financial Bid
- 9.0 **BID FORM**
- 9.01 The Bidder shall submit Bid Form with the Bidding Documents.

9.02 **EMD**

Pursuant to Clause 8.0(a) above, the bidder shall furnish, as part of its bid, an EMD amounting to as specified in Section I. The EMD is required to protect the Purchaser against the risk of Bidder's conduct which will warrant forfeiture.

The EMD shall be denominated in any of the following forms:

- (a) Bank Guarantee drawn in favour of BSES Yamuna Power Ltd, payable at Delhi or
- (b) Fixed Deposit (lien marked in favour of BSES Yamuna Power Limited) payable at Delhi.

(c) Online transfer of requisite amount through IMPS/NEFT/RTGS to BYPL account mentioned herein in Appendix II - **BYPL BANK DETAILS WITH IFSC CODE**.

EMD shall be valid for One Hundred Twenty (120) days after the due date of submission drawn in favour of BSES Yamuna Power Ltd.

The EMD may be forfeited in the case of:

(a) the Bidder withdraws its bid during the period of specified bid validity

or

- (b) the case of a successful Bidder, if the Bidder does not
 - (i) Accept the Purchase Order, or
 - (ii) Furnish the required performance security BG.

10.0 **BID PRICES**

- 10.01 Bidders shall quote for the entire Scope of Supply/Work with a break-up of prices for individual items. The total Bid Price shall also cover all the Supplier's obligations mentioned in or reasonably to be inferred from the Bidding Documents in respect of Design, Supply, and Transportation to the site, all in accordance with the requirement of the Bidding Documents. The Bidder shall complete the appropriate Price Schedules included herein, stating the Unit Price for each item & total Price.
- 10.02 The prices offered shall be inclusive of all costs as well as Duties, Taxes or Levies paid or payable during the execution of the supply work, a breakup of price constituents, should be there.
- 10.03 Prices quoted by the Bidder shall be "Firm" and not subject to any price adjustment during the performance of the Contract. A Bid submitted with an adjustable price/ Price Variation Clause will be treated as non-responsive and rejected.

11.0 BID CURRENCIES

11.01 Prices shall be guoted in Indian Rupees Only.

12.0 PERIOD OF VALIDITY OF BIDS

- 12.01 Bids shall remain valid for 120 days from the due date of submission of the Bid.
- 12.02 Notwithstanding Clause 12.01 above, the Purchaser may solicit the Bidder's consent to an extension of the Period of Bid Validity. The request and the responses thereto shall be made in writing and sent by post/courier.

13.0 **ALTERNATIVE BIDS**

13.01 Bidders shall submit Bids, which comply with the Bidding Documents. Alternative Bids will not be considered. The attention of Bidders is drawn to the provisions regarding the rejection of Bids in the terms and conditions, which are not substantially responsive to the requirements of the Bidding Documents.

INFORMATION TO BIDDER (ITB) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 12 of 17	Bidders seal & Signature
--	-----------------------------	--------------------------

14.0 FORMAT AND SIGNING OF BID

- 14.01 The original Bid Form and accompanying documents, must be received by the Purchaser at the date, time and place specified pursuant to Clauses 15.0 and 16.0.
- 14.02 The original Bid shall be typed or written in indelible ink and shall be signed by the Bidder or a person or persons duly authorized to sign on behalf of the Bidder. Such authorization shall be indicated by written Power-of-Attorney accompanying the Bid. The Bid submitted on behalf of companies registered with the Indian Companies Act, for the time being in force, shall be signed by persons duly authorized to submit the Bid on behalf of the Company and shall be accompanied by certified true copies of the resolutions, extracts of Articles of Association, special or general Power of Attorney etc. to show clearly the title, authority and designation of persons signing the Bid on behalf of the Company. Satisfactory evidence of the authority of the person signing on behalf of the Bidder shall be furnished with the bid. A bid by a person who affixes to his signature the words 'President', 'Managing Director', 'Secretary', 'Agent' or other designations without disclosing his principal will be rejected.

The Bidder's name stated on the Proposal shall be the exact legal name of the firm.

14.03 The Bid shall contain no interlineations, erasures or overwriting except as necessary to correct errors made by the Bidder, in which case such corrections shall be initiated by the person or persons signing the Bid.

D. SUBMISSION OF BIDS

15.0 **SEALING AND MARKING OF BIDS**

- 15.01 Bid submission: Bids have to be mandatorily submitted only through the e-procurement portal of BSES Delhi. Bids submitted through any other form/ route shall not be admissible.
- 15.02 However, documents that necessarily have to be submitted in originals like EMD or Tender Fee (in the form of BG/ DD /FD as applicable) and any other documents mentioned in the tender documents have to be submitted at the BYPL office before the due date & time of submission. The Technical Documents and the EMD shall be enclosed in a sealed envelope and the said envelope shall be superscribed with "Technical Bid & EMD". All the envelopes should bear the Name and Address of the Bidder and mark for the Original. The envelopes should be superscribed with "Tender No. & Due date of opening".
- 15.03 The Bidder has the option of sending the Bids in person. Bids submitted by Email/Telex/Telegram /Fax will be rejected. No request from any Bidder to the Purchaser to collect the proposals from Courier/Airlines/Cargo Agents etc. shall be entertained by the Purchaser.

16.0 **DEADLINE FOR SUBMISSION OF BIDS**

- 16.01 The Bid must be received by the Purchaser on or before the due date & time of submission.
- 16.02 The Purchaser may, at its discretion, extend the deadline for the submission of Bids by amending the Bidding Documents in accordance with Clause 6.0, in which case all rights and obligations of the Purchaser and Bidders previously subject to the deadline will thereafter be subject to the deadline as extended.

17.0 **ONE BID PER BIDDER**

17.01 Each Bidder shall submit only one Bid by itself. No Joint venture is acceptable. A Bidder who submits

INFORMATION TO BIDDER (ITB)	Page 13 of 17	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		

or participates in more than one Bid will cause all those Bids to be rejected.

18.0 **LATE BIDS**

18.01 No Bid will be received by the Purchaser after the deadline for submission of Bids prescribed by the Purchaser, pursuant to Clause 16.0.

19.0 MODIFICATIONS AND WITHDRAWAL OF BIDS

19.01 The Bidder is not allowed to modify or withdraw its Bid after the Bid's due date & time of submission subject to any corrigendum/addendum/modifications in the tender documents uploaded to the website.

E. EVALUATION OF BID

20.0 **PROCESS TO BE CONFIDENTIAL**

Information relating to the examination, clarification, evaluation and comparison of Bids and recommendations for the award of a contract shall not be disclosed to Bidders or any other persons not officially concerned with such process. Any effort by a Bidder to influence the Purchaser's processing of Bids or award decisions may result in the rejection of the Bidder's Bid.

21.0 CLARIFICATION OF BIDS

To assist in the examination, evaluation and comparison of Bids, the Purchaser may, at its discretion, ask the Bidder for a clarification of its Bid. All responses to requests for clarification shall be in writing and no change in the price or substance of the Bid shall be sought, offered or permitted.

22.0 PRELIMINARY EXAMINATION OF BIDS / RESPONSIVENESS

- 22.01 Purchaser will examine the Bids to determine whether they are complete, whether any computational errors have been made, whether required sureties have been furnished, whether the documents have been properly signed and whether the Bids are generally in order. Purchaser may ask for submission of original documents to verify the documents submitted in support of qualification criteria.
- 22.02 Arithmetical errors will be rectified on the following basis. If there is a discrepancy between the unit price and the total price per item that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price per item will be corrected. If there is a discrepancy between the Total Amount and the sum of the total price per item, the sum of the total price per item shall prevail and the Total Amount will be corrected.
- 22.03 Prior to the detailed evaluation, Purchaser will determine the substantial responsiveness of each Bid to the Bidding Documents including production capability and acceptable quality of the Goods offered. A substantially responsive Bid is one, which conforms to all the terms and conditions of the Bidding Documents without material deviation.
- 22.04 Bid determined as not substantially responsive will be rejected by the Purchaser and/or the Purchaser and may not subsequently be made responsive by the Bidder by correction of the non-conformity.

23.0 **EVALUATION AND COMPARISON OF BIDS**

INFORMATION TO BIDDER (ITB) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 14 of 17	Bidders seal & Signature
[RFX Number: 2200000026]		

- 23.01 The evaluation of Bids shall be done based on the delivered cost competitiveness basis.
- 23.02 The evaluation of the Bids shall be a stage-wise procedure. The following stages are identified for evaluation purposes: In the first stage, the Bids will be subjected to a responsiveness check. The Technical & qualifying Proposals and the Conditional ties of the Bidders will be evaluated.
 - Subsequently, the Financial Proposals along with Supplementary Financial Proposals, if any, of Bidders with Techno-commercially Acceptable Bids shall be considered for final evaluation.
- 23.03 The Purchaser's evaluation of a Bid will take into account, in addition to the Bid price, the following factors, in the manner and to the extent indicated in this Clause:
 - (a) Delivery Schedule
 - (b) Conformance to Qualifying Criteria
 - (c) Deviations from Bidding Documents

Bidders shall base their Bid price on the terms and conditions specified in the Bidding Documents.

The cost of all quantifiable deviations and omissions from the specification, terms and conditions specified in the Bidding Documents shall be evaluated. The Purchaser will make its own assessment of the cost of any deviation to ensure a fair comparison of Bids.

23.04 Any price adjustments that result from the above procedures shall be added for comparative evaluation only to arrive at an "Evaluated Bid Price". Bid Prices quoted by Bidders shall remain unaltered.

F. AWARD OF CONTRACT

24.0 **CONTACTING THE PURCHASER**

- 24.01 If any Bidder wishes to contact the Purchaser on any matter related to the Bid, from the time of Bid opening to the time of contract award, the same shall be done in writing only.
- 24.02 Any effort by a Bidder to influence the Purchaser and/or in the Purchaser's decisions in respect of Bid evaluation, Bid comparison or Contract Award, will result in the rejection of the Bidder's Bid.

25.0 THE PURCHASER'S RIGHT TO ACCEPT ANY BID AND TO REJECT ANY OR ALL BIDS

Submission of bids shall not automatically construe qualification for evaluation. The Purchaser reserves the right to accept or reject any Bid and to annul the Bidding process and reject all Bids at any time prior to the award of the Contract, without thereby incurring any liability to the affected Bidder or Bidders or any obligation to inform the affected Bidder or Bidders of the grounds for the Purchaser's action.

26.0 AWARD OF CONTRACT

The Purchaser will award the Contract to the successful Bidder whose Bid has been Determined to be the lowest-evaluated responsive Bid, provided further that the Bidder has been determined to be qualified to satisfactorily perform the Contract. Purchaser reserves the right to award the order to other bidders in the tender, provided it is required for the timely execution of the project & provided he agrees to come to the lowest rate. Purchaser reserves the right to distribute the entire tender quantity at its own discretion without citing any reasons thereof.

INFORMATION TO BIDDER (ITB) NIT NO: CMC/BY/24-25/RS/SkS/SV/09	Page 15 of 17	Bidders seal & Signature
[RFx Number: 2200000026]		

27.0 THE PURCHASER'S RIGHT TO VARY QUANTITIES

The Purchaser reserves the right to vary the quantity i.e. increase or decrease the numbers/quantities without any change in terms and conditions during the execution of the Order.

28.0 LETTER OF INTENT/ NOTIFICATION OF AWARD

The letter of intent/ Notification of Award shall be issued to the successful Bidder whose bids have been considered responsive, techno-commercially acceptable and evaluated to be the lowest (L1). The successful Bidder shall be required to furnish a letter of acceptance within 7 days of the issue of the letter of intent /Notification of Award by Purchaser.

29.0 **PERFORMANCE BANK GUARANTEE (PBG)**

To be submitted within twenty-eight (28) days from the date of issuance of the Letter of Intent/Award/PO. Bidder shall submit the performance bank guarantee (PBG) equivalent to 10% of the PO value (including GST) valid for a period of 30 months from the date of last receipts at site/stores plus 3 months claim period.

30.0 CORRUPT OR FRAUDULENT PRACTICES

- 30.01 The Purchaser requires that the Bidders observe the highest standard of ethics during the procurement and execution of the Project. In pursuance of this policy, the Purchaser:
 - (a) Defines, for this provision, the terms set forth below as follows:
 - (i) "Corrupt practice" means behaviour on the part of officials in the public or private sectors by which they improperly and unlawfully enrich themselves and/or those close to them, or induce others to do so, by misusing the position in which they are placed, and it includes the offering, giving, receiving, or soliciting of anything of value to influence the action of any such official in the procurement process or contract execution; and
 - (ii) "Fraudulent practice" means a misrepresentation of facts to influence a procurement process or the execution of a contract to the detriment of the Purchaser, and includes collusive practice among Bidders (before or after Bid submission) designed to establish Bid prices at artificial non -competitive levels and to deprive the Purchaser of the benefits of free and open competition.
 - (b) Will reject a proposal for award if it determines that the Bidder recommended for award has engaged in corrupt or fraudulent practices in competing for the contract in question;
 - (c) Will declare a firm ineligible, either indefinitely or for a stated period, to be awarded a contract if it at any time determines that the firm has engaged in corrupt or fraudulent practices in competing for, or in executing a contract.
- 30.02 Furthermore, Bidders shall be aware of the provision stated in the Terms and Conditions of the Contract.

31.0 **STATUTORY GUIDELINES & REGULATIONS**

The bidder shall make himself fully aware & familiarize himself with all applicable laws/guidelines/regulations.

32.0 **SAFETY**

INFORMATION TO BIDDER (ITB) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 16 of 17	Bidders seal & Signature
--	-----------------------------	--------------------------

Safety related requirements as mentioned in our safety Manual put on the Company's website which can be accessed at http://www.bsesdelhi.com. All bidders shall strictly abide by the guidelines provided in the safety manual at all relevant stages during the contract period.

33.0 **PRIORITY OF CONTRACT DOCUMENTS**

The several documents forming the Agreement are to be taken as mutually explanatory of one another, but in case of ambiguities or discrepancies, the same shall be explained and adjusted by the company, who shall, accordingly, issue suitable instructions thereon to the Contractor. In such event, unless otherwise provided in the agreement or explained by way of instructions by the company, as mentioned above, the priority of the documents forming the Agreement shall be as follows:

- i) Contract Agreement/Purchase Order.
- (a)Special Conditions of Contract
- (b)General Conditions of Contract
- (ii)The Letter of Acceptance/ Intent
- (iii)Agreed Minutes of the Tender Negotiation Meetings
- (iv) Agreed Minutes of the Tender Technical Meetings
- (v) The Priced Bill of Quantities
- (vi)The Technical Specifications / Scope of work
- (vii)The Tender document, including all Appendices and/or Addenda, Corrigendum the latest taking precedence.

In the event of any conflict between the above-mentioned documents, the more stringent requirement or conditions which shall be favourable to the company shall govern and the decision of the company/BYPL shall be final and binding upon the parties.



INFORMATION TO BIDDER (ITB)
NIT NO: CMC/BY/24-25/RS/SkS/SV/09
[RFx Number: 2200000026]

Page **17** of **17**

Bidders seal & Signature

BID INDEX FOR PART-A (TECHNICAL BID)

(To be filled & submitted on Bidder Letter Head, Bidders document submission should have following main categories as outlined below and should have page numbers printed at the bottom of each page with this page as page number 1. The page number should be in "Page X of Y" format. Separator with document description shall be provided before each document)

NIT & RFX No.:

Bidder's Name:

Bidder's Bid Reference No. & Date:

No. Particulars From To A.1 Bid Details 1. Bid Index for Part-A (Technical Bid) as per APPENDIX I ANNEXURE - 1.01 2. Cover Letter, If any 3. Bid Form (Unpriced) Duly Signed as per APPENDIX I ANNEXURE - 1.02 4. Tender Fee Details as per APPENDIX I ANNEXURE - 1.03 5. EMD Details as per APPENDIX I ANNEXURE - 1.04 & 1.05 6. Power-of-Attorney / Authorization Letter A.2 Technical Bid 7. Communication Details of the Bidder as per APPENDIX I ANNEXURE - 1.06 8. ANNEXURE - 1.07 8. ANNEXURE - 1.07 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 8. Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 9. Isuaranteed Technical particulars (GTP) as per specification 10. APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Devaitons (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.16 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format) 26. NIT Document complete Signed & Stamped	S.	Bid Pdf Page No.				
1. Bid Index for Part-A (Technical Bid) as per APPENDIX I ANNEXURE - 1.01 2. Cover Letter, If any 3. Bid Form (Unpriced) Duly Signed as per APPENDIX I ANNEXURE - 1.02 4. Tender Fee Details as per APPENDIX I ANNEXURE - 1.03 5. EMD Details as per APPENDIX I ANNEXURE - 1.04 & 1.05 6. Power-of-Attorney / Authorization Letter 4. Zerhanical Bid 7. Communication Details of the Bidder as per APPENDIX I ANNEXURE - 1.06 8. Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.07 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 10. Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 24. APPENDIX I ANNEXURE - 1.13 25. Product Catalogue (If applicable) 26. Manufacturer's quality assurance plan (as applicable) 27. Other drawings/ documents mentioned in technical specification 18. Testing Facilities 28. A.3 Commercial Bid 29. Company Profile/Organogram/Organization Chart & Manpower Details 29. APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 29. ACCEPTANCE of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 20. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 21. ANNEXURE - 1.17 22. ANNEXURE - 1.17 23. ANNEXURE - 1.17 24. ANNEXURE - 1.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	No.	Particulars		_		
2. Cover Letter, If any 3. Bid Form (Unpriced) Duly Signed as per APPENDIX I ANNEXURE - 1.02 4. Tender Fee Details as per APPENDIX I ANNEXURE - 1.03 5. EMD Details as per APPENDIX I ANNEXURE - 1.04 & 1.05 6. Power-of-Attorney / Authorization Letter A.2 Technical Bid 7. Communication Details of the Bidder as per APPENDIX I ANNEXURE - 1.06 8. Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.07 7. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 10. Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities 19. Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Bid 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. ACCEPTANCE of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 1.17 24. ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	A.1	Bid Details				
3. Bid Form (Unpriced) Duly Signed as per APPENDIX I ANNEXURE - 1.02 4. Tender Fee Details as per APPENDIX I ANNEXURE - 1.03 5. EMD Details as per APPENDIX I ANNEXURE - 1.04 & 1.05 6. Power-of-Attorney / Authorization Letter 4.2 Technical Bid 7. Communication Details of the Bidder as per APPENDIX I ANNEXURE - 1.06 8. Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.07 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 10. Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	1.	Bid Index for Part-A (Technical Bid) as per APPENDIX I ANNEXURE - 1.01	1			
4. Tender Fee Details as per APPENDIX I ANNEXURE - 1.03 5. EMD Details as per APPENDIX I ANNEXURE - 1.04 & 1.05 6. Power-of-Attorney / Authorization Letter 4.2 Technical Bid 7. Communication Details of the Bidder as per APPENDIX I ANNEXURE - 1.06 Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.07 Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 Schedule of Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	2.					
5. EMD Details as per APPENDIX I ANNEXURE - 1.04 & 1.05 6. Power-of-Attorney / Authorization Letter 7. Communication Details of the Bidder as per APPENDIX I ANNEXURE - 1.06 8. Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.07 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) as per Specification) as per APPENDIX I ANNEXURE - 1.13 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Bid 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)						
6. Power-of-Attorney / Authorization Letter A.2 Technical Bid 7. Communication Details of the Bidder as per APPENDIX I ANNEXURE - 1.06 8. Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.07 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)						
7. Communication Details of the Bidder as per APPENDIX I ANNEXURE - 1.06 8. Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.07 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Company Profile/Organogram/Organization Chart & Manpower Details 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)						
7. Communication Details of the Bidder as per APPENDIX I ANNEXURE - 1.06 8. Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.07 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 10. Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 20. APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)						
8. Manufacturer Authorization Form (as applicable) as per APPENDIX I ANNEXURE - 1.07 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 20. Undertakings as per APPENDIX I ANNEXURE - 1.15 Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 21. ACCEPTANCE OF COMMERCIAL TERMS ANDEXURE - 1.17 22. ACCEPTANCE OF COMMERCIAL TERMS AND CONDITION OF ANDEXURE - 2.05 23. Un Price Bid Duly Signed (Volume - II Price Bid Format)	A.2					
8. ANNEXURE - 1.07 9. Technical Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.08, 1.09, 1.10 10. Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities 19. Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. ANCENTRA COMMERCIAL TERMS AND COMMERCI	7.					
10. Schedule of Technical Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.11 11. Guaranteed Technical particulars (GTP) as per specification 12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. ACCEPTANCE OF APPENDIX I ANNEXURE - 1.16 24. ACCEPTANCE OF APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	8.	ANNEXURE - 1.07				
APPENDIX I ANNEXURE - 1.11 Guaranteed Technical particulars (GTP) as per specification All Drawings as per specification Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 Product Catalogue (If applicable) Manufacturer's quality assurance plan (as applicable) Testing Facilities A.3 Commercial Bid Decompany Profile/Organogram/Organization Chart & Manpower Details Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 Undertakings as per APPENDIX I ANNEXURE - 1.15 Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 Un Price Bid Duly Signed (Volume - II Price Bid Format)	9.	The state of the s				
12. All Drawings as per specification 13. Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)		APPENDIX I ANNEXURE - 1.11				
Type Test Reports (Sequence of Tests shall be strictly in accordance with relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	11.	Guaranteed Technical particulars (GTP) as per specification				
relevant IS/IEC) as per APPENDIX I ANNEXURE - 1.12 14. Sample Submission Details (If applicable as per Specification) as per APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	12.					
APPENDIX I ANNEXURE - 1.13 15. Product Catalogue (If applicable) 16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	13.					
16. Manufacturer's quality assurance plan (as applicable) 17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	14.					
17. Other drawings/ documents mentioned in technical specification 18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	15.	Product Catalogue (If applicable)				
18. Testing Facilities A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	16.	Manufacturer's quality assurance plan (as applicable)				
A.3 Commercial Bid 19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	17.	Other drawings/ documents mentioned in technical specification				
19. Company Profile/Organogram/Organization Chart & Manpower Details 20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)						
20. Commercial Qualifying Criteria Compliance Index & Documents as per APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)						
20. APPENDIX I ANNEXURE - 1.14 21. Undertakings as per APPENDIX I ANNEXURE - 1.15 22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	19.					
22. Schedule of Commercial Deviations (along with soft editable Excel copy) as per APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	20.					
22. APPENDIX I ANNEXURE - 1.16 23. Acceptance form for participation in reverse auction event as per APPENDIX I ANNEXURE - 1.17 24. Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	21.	Undertakings as per APPENDIX I ANNEXURE - 1.15				
ANNEXURE - 1.17 Acceptance of Commercial Terms and Conditions as per APPENDIX II ANNEXURE - 2.05 Un Price Bid Duly Signed (Volume - II Price Bid Format)	22.					
ANNEXURE - 2.05 25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	23.					
25. Un Price Bid Duly Signed (Volume - II Price Bid Format)	24.					
	25.					

APPENDIX I	Page 1 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09	-	
[RFx Number: 2200000026]		

BID FORM

Tο

Head of Department Contracts & Material Deptt. BSES Yamuna Power Ltd Shaktikiran Building, Karkardooma, Delhi 110032

Sir,

- 1. We understand that BYPL is desirous of procuring...... for its licensed distribution network area in Delhi.
- 2. Having examined the Bidding Documents for the above-named works, we the undersigned, offer to deliver the goods in full conformity with the Terms and Conditions and technical specifications for the sum indicated in the Price Bid or such other sums as may be determined in accordance with the terms and conditions of the contract. The amounts are in accordance with the Price Schedules attached herewith and are made part of this bid.
- 3. If our Bid is accepted, we undertake to deliver the entire goods as per the delivery schedule mentioned in Section IV from the date of award of the purchase order/letter of intent.
- 4. If our Bid is accepted, we will furnish a performance bank guarantee for due performance of the Contract in accordance with the Terms and Conditions.
- 5. We agree to abide by this Bid for 120 days from the due date of bid submission and it shall remain binding upon us and may be accepted at any time before the expiration of that period.
- 6. We declare that we have studied the provision of Indian Laws for the supply/services of equipment's/materials and the prices have been quoted accordingly.
- 7. Unless and until Letter of Intent is issued, this Bid, together with your written acceptance thereof, shall constitute a binding contract between us.
- 8. We understand that you are not bound to accept the lowest or any bid you may receive.
- 9. There is provision for Resolution of Disputes under this Contract, by the Laws and Jurisdiction of Contract.

Dated this	day of	20XX
Cianakuus	7.	the comoring of
Signature		the capacity of
		duly authorized to sign for and on behalf of
(IN BLOCK CAPI	TALS)	

APPENDIX I
NIT NO: CMC/BY/24-25/RS/SkS/SV/09
[REx Number: 2200000026]

Page **2** of **21**

Bidders seal & Signature

TENDER FEE DETAILS

: 1,180/- (One Thousand One Hundred Eighty Only)

	-		
b. Mode of Payment	: DD or online transfer through IMF	PS/NEFT/RTGS (select any one)	

c. DD /UTR No. (As applicable) :

a. Amount (Rs.)

d. Dated :

e. Bidders Bank Account No. :

f. Name of the Bank :

g. Address of the Bank :

h. IFSC Code of the Bank :

EMD DETAILS

a. EMD Amount (Rs.)	:
b. Mode of Payment	: BG/FD/online transfer through IMPS/NEFT/RTGS (select any one)
c. BG/FD/UTR No. (As applicable	e):
d. Dated	:
e. BG valid up to	:
f. BG Claim period up to	
g. Bidders Bank Account No.	
h. Name of the Bank	
i. Address of the Bank	
j. IFSC Code of the Bank	:

(FORMAT FOR EMD BANK GUARANTEE)

(To be issued in a Non-Judicial Stamp Paper of Rs.50/-purchased in the name of the bank)

Whereas [name of the Bidder] (hereinafter called the "Bidder") has submitted its bid dated [date of

submission of bid] for the supply of [name and/or description of the goods] (hereafter called the "Bid").
KNOW ALL PEOPLE by these presents that WE [name of bank] at [Branch Name and address], having our registered office at [address of the registered office of the bank] (hereinafter called the "Bank"), are bound unto BSES Yamuna Power Ltd., with its Corporate Office at Shaktikiran Building, Karkardooma, Delhi - 110032, (hereinafter called - the "Purchaser") in the sum of Rs
Sealed with the Common Seal of the said Bank this day of 20
The conditions of this obligation are:
If the Bidder withdraws its Bid during the period of bid validity specified by the Bidder on the Bid Form; or
 If the Bidder, having been notified of the acceptance of its Bid by the Purchaser during the period of bid validity: (a) Fails or refuses to execute the Contract Form, if required; or (b) Fails or refuses to furnish performance security, In accordance with the Instructions to Bidders/Terms and Conditions;
We undertake to pay to the Purchaser up to the above amount upon receipt of its first written demand, without the Purchaser having to substantiate its demand, provided that is its demand the purchaser will note that amount claimed by it is due to it, owing to the occurrence of one or both of the two condition(s), specifying the occurred condition or condition(s).
This guarantee will remain in force up to and including One Hundred Twenty (120) days after the due date of submission bid, and any demand in respect thereof should reach the Bank not later than the above date.
(Stamp & signature of the bank)

APPENDIX I NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 5 of 21	Bidders seal & Signature	
---	----------------------------	--------------------------	--

Signature of the witness

COMMUNICATION DETAILS OF THE BIDDER

S. No.	Designation	Name	Mobile No.	E-mail id
1	CEO / MD			
2	Sales / Marketing Head			
3	Sales Representative / Key Account Manager (KAM)			
4	Technical Head			
5	Manufacturer Plant / Operations Head			
6	Post Order Execution In Charge			
7	Authorized contact person (Primary responsibility for the Bid)			
8	Authorized contact person (Secondary responsibility for the Bid)			

APPENDIX I	Page 6 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		

MANUFACTURER AUTHORIZATION FORM (To be submitted on OEM's Letter Head)

Date: Tender No.:
То
Head of Department Contracts & Material Deptt. BSES Yamuna Power Ltd Shaktikiran Building, Karkardooma, Delhi 110032
Sir,
WHEREAS M/s. [name of OEM], who are official manufacturers of having factories at [address of
OEM] do hereby authorize M/s [name of bidder] to submit a Bid in relation to the Invitation for Bids
indicated above, the purpose of which is to provide the following Goods, manufactured by us
and to subsequently negotiate and
sign the Contract.
We hereby extend our full guarantee and warranty by the Conditions of the Contract or as mentioned elsewhere in the Tender Document, concerning the Goods offered by the above firm in reply to this Invitation for Bids.
We hereby confirm that in case, the channel partner fails to provide the necessary services as per the Tender Document referred above, M/s [name of OEM] shall provide standard warranty on the materials supplied against the contract. The warranty period and inclusion/exclusion of parts in the warranty shall remain the same as defined in the contract issued to our channel partner against this tender.
Yours Sincerely, For
Authorized Signatory

APPENDIX I	Page 7 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]		8


	QUALIFYING CRITERIA COMPLIANCE INDEX - TECHNICAL CRITERIA								
S	Qualifying Criteria Description as per section	Documentary Proof	Documentary Proof Enclosed on Bid Page No.						
No	1 clause 2.00	Description	From	То					
1									
2									
3									
4									
5									



APPENDIX I	Page 8 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		

L	IST O	F PUR	CHASE	ORDERS	EXECU		& DELI\ QUIRE		TAILS IN	N SUPPO	RT OF Q	UALIFY	ING
S No	Item Details				PO & Execution Details				Customer Name	End User (shall be Utility/ SEB's/ PSU's)	PO copy /Deli compl certific Invoice enclosed Page	very letion cates/ Copies d on Bid	
	Item	Model	Voltage Rating (kV)	Current Rating (A)	PO No	PO Date	PO Qty	Executed Qty	Execution Year		name and details	From	То
Tota	al			A			Σ	Σ	•				

Note – Only items relevant as per qualifying requirements should be included in the list.




ANNEXURE - 1.10

	LIST OF PERFORMANCE CERTIFICATES IN SUPPORT OF QUALIFYING REQUIREMENT															
S No	Item Details				PO No			No Commissioning		Performance Certificate Issue Date	Performance Certificate Issued By End User		act Det uing Pe		Enclo on E Page	Bid
	Item	Model	Voltage Rating (kV)	Current Rating (A)		Qty.	Date		(Utility/SEB/Govt Org.)	Name	Email	Mobile	From	То		
								\wedge								
Tot	al					Σ										

Note -

- 1. Only items relevant as per qualifying requirement should be included in the list.
- 2. Only Performance certificates issued by End User (utilities/ SEB's/PSU's only) will be accepted as per qualifying requirement.



SCHEDULE OF DEVIATIONS - TECHNICAL

Vendor shall refrain from taking any deviations on this TENDER. Still, in case of any deviations, all such deviations from this tender shall be set out by the Bidder, Clause by Clause in this schedule and submit the same as a part of the Technical Bid.

Unless **specifically** mentioned in this schedule, the tender shall be deemed to confirm the BYPL's specifications:

Technical Deviations:-

S. No.	NIT Pdf Page No.	NIT Clause No.	NIT Clause Descriptions	Details of Clarification/deviation with justifications

Note – Please enclose detailed GTP and drawings as per specification after the technical deviation sheet

Seal	l of	the	Bid	der:
------	------	-----	-----	------

Signature:

Name:

TY	TYPE TEST REPORTS (SEQUENCE OF TESTS SHALL BE STRICTLY IN ACCORDANCE WITH RELEVANT IS/IEC)								
S No	Test Description	escription Standard Standard Testing Report		andard Standard Testing Report	Standard Standard Testing Report		Date of Issue of Report	Report E on Bid Pa	
			Clause No.	Lab	Number	Кероп	From	То	
1									
2									
3									
4									
5									
6					A				
7									



APPENDIX I	Page 12 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09	-	_
[RFx Number: 2200000026]		

ANNEXURE - 1.13

	SAMPLE SUBMISSION DETAILS (IF APPLICABLE AS PER SPECIFICATION)						
S No	Description	Bidder's Response					
1	Samples submitted with the bid	Yes/No					
1	Sample Type -1						
1.1	Model Number						
1.2	Number of samples						
2	Sample Type -2						
2.1	Model Number						
2.2	Number of samples						



APPENDIX I	Page 13 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		

QUALIFYING CRITERIA COMPLIANCE INDEX - COMMERCIAL CRITERIA				
S No	Qualifying Criteria Description as per section 1 clause 2.00	Documentary Proof Description	Documentary Proof Enclosed on Bid Page No.	
			From	То
1				
2				
3				



APPENDIX I	Page 14 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		

UNDERTAKINGS (To be submitted on Bidders Letter Head)

Date:
Tender No.:
То
Head of Department Contracts & Material Deptt. BSES Yamuna Power Ltd Shaktikiran Building, Karkardooma, Delhi 110032
Sir,
We M/s [name of bidder], do hereby undertake that
• [name of bidder] has "No Litigation" pending with the BYPL or its Group/Associates Companies as
on the date of bid opening.
• [name of bidder] has not been blacklisted/debarred by any central/state government
institution/Electricity utilities as on the date of bid opening.
• [name of bidder] shall comply with all the statuary compliances as per the laws/rules etc. before
the start of the supply/work.
Yours Sincerely,
Authorized Signatory

APPENDIX I NIT NO: CMC/BY/24-25/RS/SkS/SV/09	Page 15 of 21	Bidders seal & Signature
[RFx Number: 2200000026]		

SCHEDULE OF DEVIATIONS - COMMERCIAL

Vendor shall refrain from taking any deviations on this TENDER. Still, in case of any deviations, all such deviations from this tender shall be set out by the Bidder, Clause by Clause in this schedule and submit the same as a part of the Technical Bid.

Unless **specifically** mentioned in this schedule, the tender shall be deemed to confirm the BYPL's specifications:

Commercial Deviations:-

S. No.	NIT Pdf Page No.	NIT Clause No.	NIT Clause Descriptions	Details of Clarification/deviation with justifications

By signing this document we hereby withdraw all the deviations whatsoever taken anywhere in this bid document and comply with all the terms and conditions, technical specifications, scope of work etc. as mentioned in the standard document except those mentioned above.

Seal of the Bidder:			
Signature:			
Name:			

ACCEPTANCE FORM FOR PARTICIPATION IN REVERSE AUCTION EVENT

(To be signed and stamped by the bidder)

BSES Yamuna Power Ltd (hereinafter referred to as **"BYPL"**) intends to use the reverse auction through the SAP-SRM tool as an integral part of the entire tendering process. All the bidders who are found as techno commercial qualified based on the tender requirements shall be eligible to participate in the reverse auction event.

The following terms and conditions are deemed as accepted by the bidder on participation in the bid event:

- 1. BYPL shall provide the user ID and password to the authorized representative of the bidder. (Authorization letter in lieu of the same be submitted along with the signed and stamped acceptance form)
- 2. BYPL will make every effort to make the bid process transparent. However, the award decision by BYPL would be final and binding on the bidder.
- 3. The bidder agrees to non-disclosure of trade information regarding the purchase, identity of BYPL, bid process, bid technology, bid documentation, bid details, etc.
- 4. The bidder is advised to understand the auto bid process to safeguard themselves against any possibility of non-participation in the auction event.
- 5. In case of bidding through internet medium, bidders are further advised to ensure availability of the entire infrastructure as required at their end to participate in the auction event. Inability to bid due to telephone line glitches, internet response issues, software or hardware hangs; power failure or any other reason shall not be the responsibility of BYPL.
- 6. In case of intranet medium, BYPL shall provide the infrastructure to bidders, further, BYPL has sole discretion to extend or restart the auction event in case of any glitches in infrastructure observed which has restricted the bidders from submitting the bids to ensure fair & transparent competitive bidding. In case an auction event is restarted, the best bid already available in the system shall become the start price for the new auction.
- 7. In case the bidder fails to participate in the auction event due to any reason whatsoever, it shall be presumed that the bidder has no further discounts to offer and the initial bid as submitted by the bidder as a part of the tender shall be considered as the bidder's final no regret offer. Any offline price bids received from a bidder in lieu of non-participation in the auction event shall be outright rejected by BYPL.
- 8. The bidder shall be prepared with competitive price quotes on the day of the reverse auction event.
- 9. The prices as quoted by the bidder during the auction event shall be inclusive of all the applicable taxes, duties and levies and shall be FOR Landed Cost basis at the BYPL site.
- 10. The prices submitted by a bidder during the auction event shall be binding on the bidder.
- 11. No requests for time extension of the auction event shall be considered by BYPL.
- 12. The original price bids of the bidders shall be reduced on pro-rata basis against each line item based on the final all-inclusive prices offered during the conclusion of the auction event to arrive at the contract amount.

Signature & seal of the Bidder

APPENDIX I	Page 17 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	J	

VENDOR CODE OF CONDUCT

Purchaser is committed to conducting its business in an ethical, legal and socially responsible manner. To encourage compliance with all legal requirements and ethical business practices, Purchaser has established this Vendor Code of Conduct (the "Code") for Purchaser's Vendors. For the purposes of this document, "Vendor" means any company, corporation or other entity that sells, or seeks to sell goods or services, to Purchaser, including the Vendor's employees, agents and other representatives.

Fundamental to adopting the Code is the understanding that a business, in all of its activities, must operate in full compliance with the laws, rules and regulations of the countries in which it operates. This Code encourages Vendors to go beyond legal compliance, drawing upon internationally recognized standards, in order to advance social and environmental responsibility.

I. Labour and Human Rights

Vendors must uphold the human rights of workers, and treat them with dignity and respect as understood by the international community.

- Fair Treatment Vendors must be committed to a workplace free of harassment. Vendors shall not threaten workers with or subject them to harsh or inhumane treatment, including sexual harassment, sexual abuse, corporal punishment, mental coercion, physical coercion, verbal abuse or unreasonable restrictions on entering or exiting company provided facilities.
- Antidiscrimination Vendors shall not discriminate against any worker based on race, colour, age, gender, sexual orientation, ethnicity, disability, religion, political affiliation, union membership, national origin, or marital status in hiring and employment practices such as applications for employment, promotions, rewards, access to training, job assignments, wages, benefits, discipline, and termination. Vendors shall not require a pregnancy test or discriminate against pregnant workers except where required by applicable laws or regulations or prudent for workplace safety. In addition, Vendors shall not require workers or potential workers to undergo medical tests that could be used in a discriminatory way except where required by applicable law or regulation or prudent for workplace safety.
- Freely Chosen Employment Forced, bonded or indentured labour or involuntary prison labour is not to be used. All work will be voluntary, and workers should be free to leave upon reasonable notice. Workers shall not be required to hand over government-issued identification, passports or work permits as a condition of employment.
- . Prevention of Under Age Labor Child labour is strictly prohibited. Vendors shall not employ children. The minimum /age for employment or work shall be 15 years of age, the minimum age for employment in that country, or the age for completing compulsory education in that country, whichever is higher. This Code does not prohibit participation in legitimate workplace apprenticeship programs that are consistent with Article 6 of ILO Minimum Age Convention No. 138 or light work consistent with Article 7 of ILO Minimum Age Convention No. 138.
- Juvenile Labor Vendors may employ juveniles who are older than the applicable legal minimum age for employment but are younger than 18 years of age, provided they do not perform work likely to jeopardize their health, safety, or morals, consistent with ILO Minimum Age Convention No. 138.
- . Minimum Wages Compensation paid to workers shall comply with all applicable wage laws, including those relating to minimum wages, overtime hours and legally mandated benefits. Any Disciplinary wage deductions are to conform to local law. The basis on which workers are being paid is to be clearly conveyed to them in a timely manner.
- Working Hours Studies of good manufacturing practices clearly link worker strain to reduced productivity, increased turnover and increased injury and illness. Work weeks are not to exceed maximum set by local law. Further, a work week should not be more than 60 hours per week, including overtime,

APPENDIX I	Page 18 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]		
[KLX Nulliber: 2200000020]		

except in emergency or unusual situations. Workers should be allowed at least one day off per sevenday week.

• Freedom of Association - Open communication and direct engagement between workers and management are the most effective ways to resolve workplace and compensation issues. Vendors are to respect the rights of workers to associate freely and to communicate openly with management regarding working conditions without fear of reprisal, intimidation or harassment. Workers' rights to join labour unions seek representation and or join worker's councils in accordance with local laws should be acknowledged.

II. Health and Safety

Vendors must recognize that in addition to minimizing the incidence of work-related injury and illness, a safe and healthy work environment enhances the quality of products and services, consistency of production and worker retention and morale. Vendors must also recognize that ongoing worker input and education are essential to identifying and solving health and safety issues in the workplace.

The health and safety standards are:

- Occupational Injury and Illness Procedures and systems are to be in place to prevent, manage, track and report occupational injury and illness, including provisions to a) encourage worker reporting; b) classify and record injury and illness cases; c) provide necessary medical treatment; d) investigate cases and implement corrective actions to eliminate their causes; and e) facilitate return of workers to work.
- Emergency Preparedness Emergency situations and events are to be identified and assessed, and their impact minimized by implementing emergency plans and response procedures, including emergency reporting, employee notification and evacuation procedures, worker training and drills, appropriate fire detection and suppression equipment, adequate exit facilities and recovery plans.
- Occupational Safety Worker exposure to potential safety hazards (e.g., electrical and other energy sources, fire, vehicles, and fall hazards) is to be controlled through proper design engineering and administrative controls, preventative maintenance and safe work procedures (including lockout/ragout), and ongoing safety training. Where hazards cannot be adequately controlled by these means, workers are to be provided with appropriate, well-maintained, personal protective equipment. Workers shall not be disciplined for raising safety concerns.
- Machine Safeguarding Production and other machinery are to be evaluated for safety hazards. Physical guards, interlocks and barriers are to be provided and properly maintained where machinery presents an injury hazard to workers.
- . Industrial Hygiene Worker exposure to chemical, biological and physical agents is to be identified, evaluated, and controlled. Engineering or administrative controls must be used to control overexposures. When hazards cannot be adequately controlled by such means, worker health is to be protected by appropriate personal protective equipment programs.
- . Sanitation, Food, and Housing Workers are to be provided with ready access to clean toilet, facilities potable water and sanitary food preparation, storage, and eating facilities. Worker dormitories provided by the Participant or a labour agent are to be maintained clean and safe, and provided by the Participant or a labour egress, hot water for bathing and showering, and adequate heat and ventilation and reasonable personal space along with reasonable entry and exit privileges.
- Physically Demanding Work Worker exposure to the hazards of physically demanding tasks, including manual material handling and heavy or repetitive lifting, prolonged standing and highly repetitive or forceful assembly tasks is to be identified, evaluated and controlled.

III. Environmental

Vendors should recognize that environmental responsibility is integral to producing world class products In manufacturing operations, adverse effects on the environment and natural resources are to be minimized while safeguarding the health and safety of the public.

APPENDIX I	Page 19 of 21	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		

The environmental standards are:

- Product Content Restrictions Vendors are to adhere to applicable laws and regulations regarding prohibition or restriction of specific substances including labeling laws and regulations for recycling and disposal. In addition, Vendors are to adhere to all environmental requirements specified by Purchaser.
- Chemical and Hazardous Materials -Chemical and other materials posing a hazard if released to the environment are to be identified and managed to ensure their safe handling, movement storage, recycling or reuse and disposal.
- Air Emissions Air emissions of volatile organic chemicals, aerosols, corrosives, particulates, ozone depleting chemicals and combustion by-products generated from operations are to be characterized, monitored, controlled and treated as required prior to discharge.
- Pollution Prevention and Resource Reduction -Waste of all types, including water and energy, are to be reduced or eliminated at the source or by practices such as modifying production, maintenance and facility processes, materials substitution, conservation, recycling and re-using materials.
- . Wastewater and Solid Waste Wastewater and solid waste generated from operations industrial processes and sanitation facilities are to be monitored, controlled and treated as required prior to discharge or disposal.
- Environmental Permits and Reporting All required environmental permits (e.g. discharge monitoring) and registrations are to be obtained, maintained and kept current and their operational and reporting requirements are to be followed.

IV. Ethics

Vendors must be committed to the highest standards of ethical conduct when dealing with workers, Vendors, and customers.

- Corruption, Extortion, or Embezzlement Corruption, extortion, and embezzlement, in any form, are strictly prohibited. Vendors shall not engage in corruption, extortion or embezzlement in any form and violations of this prohibition may result in immediate termination as a Vendor and in legal action.
- Disclosure of Information Vendors must disclose information regarding their business activities, structure financial situation, and performance in accordance with applicable laws and regulations and prevailing industry practices.
- No Improper Advantage Vendors shall not offer or accept bribes or other means of obtaining undue or improper advantage.
- Fair Business, Advertising, and Competition Vendors must uphold fair business standards in advertising, sales, and competition.
- Business Integrity The highest standards of integrity are to be expected in all business interactions. Participants shall prohibit any and all forms of corruption, extortion and embezzlement. Monitoring and enforcement procedures shall be implemented to ensure conformance.
- Community Engagement Vendors are encouraged to engage the community to help foster social and economic development and to contribute to the sustainability of the communities in which they operate.
- Protection of Intellectual Property Vendors must respect intellectual property rights; safeguard customer information; and transfer of technology and know-how must be done in a manner that protects intellectual property rights.

V. Management System

Vendors shall adopt or establish a management system whose scope is related to the content of this Code. The management system shall be designed to ensure (a) compliance with applicable laws, regulations and customer requirements related to the Vendors' operations and products; (b) conformance with this Code; and (c) identification and mitigation of operational risks related to this Code. It should also facilitate continual improvement.

The management system should contain the following elements:


APPENDIX I NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 20 of 21	Bidders seal & Signature
[//		

- Company Commitment Corporate social and environmental responsibility statements affirming Vendor's commitment to compliance and continual improvement.
- Management Accountability and Responsibility Clearly identified company representative[s]responsible for ensuring implementation and periodic review of the status of the management systems.
- Legal and Customer Requirements Identification, monitoring and understanding of applicable laws, regulations and customer requirements.
- . Risk Assessment and Risk Management Process to identify the environmental, health and safety and labour practice risks associated with Vendor's operations. Determination of the relative significance for each risk and implementation of appropriate procedural and physical controls to ensure regulatory compliance to control the identified risks.
- . Performance Objectives with Implementation Plan and Measures Areas to be included in a risk assessment for health and safety are warehouse and storage facilities, plant/facilities support equipment, laboratories and test areas, sanitation facilities (bathrooms), kitchen/cafeteria and worker housing /dormitories. Written standards, performance objectives, and targets an implementation plans including a periodic assessment of Vendor's performance against those objectives.
- Training Programs for training managers and workers to implement Vendor's policies, procedures and improvement objectives.
- Communication Process for communicating clear and accurate information about Vendor's performance, practices and expectations to workers, Vendors and customers.
- Worker Feedback and Participation Ongoing processes to assess employees' understanding of and obtain feedback on practices and conditions covered by this Code and to foster continuous improvement.
- . Audits and Assessments Periodic self-evaluations to ensure conformity to legal and regulatory requirements, the content of the Code and customer contractual requirements related to social and environmental responsibility.
- Corrective Action Process Process for timely correction of deficiencies identified by internal or external assessments, inspections, investigations and reviews.
- Documentation and Records Creation of documents and records to ensure regulatory compliance and conformity to company requirements along with appropriate confidentiality to protect privacy.

The Code is modelled on and contains language from Recognized standards such as International Labour Organization Standards (ILO), Universal Declaration of Human Rights (UDHR), United Nations Convention against Corruption, and the Ethical Trading Initiative (ETI) were used as references in preparing this Code and may be useful sources of additional information

APPENDIX I NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026] Page **21** of **21**

Bidders seal & Signature



GENERAL CONDITIONS OF CONTRACT(GCC)
NIT NO: CMC/BY/24-25/RS/SkS/SV/09
[RFx Number: 2200000026]

Page **1** of **17**

Bidders seal & Signature

GENERAL CONDITIONS OF CONTRACT (GCC)-SUPPLY

The General Condition of Contract shall form a part of specifications, contract document.

1.0 General Instructions

- **1.01** All the Bids shall be prepared and submitted in accordance with these instructions.
- **1.02** Bidder shall bear all costs associated with the preparation and delivery of its Bid, and the Purchaser will in no case be responsible or liable for these costs.
- **1.03** The Bid should be submitted by the Bidder in whose name the bid document has been issued and under no circumstances it shall be transferred/sold to the other party.
- **1.04** The Purchaser reserves the right to request any additional information and also reserves the right to reject the proposal of any Bidder if, in the opinion of the Purchaser, the data in support of RFQ requirement is incomplete.
- 1.05 The Bidder is expected to examine all instructions, forms, terms & conditions and specifications in the Bid Documents. Failure to furnish all information required in the Bid Documents or submission of a Bid not substantially responsive to the Bid Documents in every respect may result in rejection of the Bid. However, the Purchaser's decision in regard to the responsiveness and rejection of bids shall be final and binding without any obligation, financial or otherwise, on the Purchaser.

2.0 Definition of Terms

- **2.01** "Purchaser" shall mean BSES Yamuna Power Limited, on whose behalf this bid enquiry is issued by its authorized representative/officers.
- "Bidder" shall mean the firm who quotes against this bid enquiry issued by the Purchaser. "Supplier" or "Supplier" shall mean the successful Bidder and/or Bidders whose bid has been accepted by the Purchaser and on whom the "Letter of Acceptance" is placed by the Purchaser and shall include his heirs, legal representatives, successors and permitted assigns wherever the context so admits.
- **2.03** "Supply" shall mean the Scope of Contract as described.
- **2.04** "Specification" shall mean collectively all the terms and stipulations contained in those portions of this bid document known as RFQ, Commercial Terms & Conditions, Instructions to Bidders, Technical Specifications and the Amendments, Revisions, Deletions or Additions, as may be made by the Purchaser from time to time.
- "Letter of Acceptance" shall mean the official notice issued by the Purchaser notifying the Supplier that his proposal has been accepted and it shall include amendments thereto, if any, issued by the Purchaser. The "Letter of Acceptance" issued by the Purchaser shall be binding on the "Supplier" The date of Letter of Acceptance shall be taken as the effective date of the commencement of contract.
- **2.06** "Month" shall mean the calendar month and "Day" shall mean the calendar day.
- **2.07** "Codes and Standards" shall mean all the applicable codes and standards as indicated in the Specification.

GENERAL CONDITIONS OF CONTRACT(GCC) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 2 of 17	Bidders seal & Signature
--	----------------------------	--------------------------

- **2.08** "Offer Sheet" shall mean Bidder's firm offer submitted to BYPL in accordance with the specification.
- **2.09** "Contract" shall mean the "Letter of Acceptance/Purchase Order" issued by the Purchaser.
- **2.10** "Contract Price" shall mean the price referred to in the "Letter of Acceptance/Purchase Order".
- **2.11** "Contract Period" shall mean the period during which the "Contract" shall be executed as agreed between the Supplier and the Purchaser in the Contract inclusive of the extended contract period for reason beyond the control of the Supplier and/or Purchaser due to force majeure.
- **2.12** "Acceptance" shall mean and deemed to include one or more of the following as will be stipulated in the specification:
 - a) The written acceptance of material by the inspector at suppliers works to ship the materials.
 - b) Acceptance of material at Purchaser site stores after its receipt and due inspection/ testing and release of material acceptance voucher.
 - c) Where the scope of the contract includes supply, acceptance shall mean issue of necessary equipment / material takeover receipt after installation & commissioning and final acceptance.

3.0 Contract Documents & Priority

3.01 Contract Documents: The terms and conditions of the contract shall consist solely of these RFQ conditions and the offer sheet.

4.0 Scope of Supply -General

- **4.01** The "Scope of Supply" shall be on the basis of Bidder's responsibility, completely covering the obligations, responsibility and supplies provided in this Bid enquiry whether implicit or explicit.
- **4.02** Bidder shall have to quote for the Bill of quantities as listed in Section IV of this RFQ.
- **4.03** Quantity variation and additional requirements if any shall be communicated to successful bidder during project execution.
- **4.04** All relevant drawings, data and instruction manuals.

5.0 Quality Assurance and Inspection

- **5.01** Immediately on award of contract, the bidder shall prepare detailed quality assurance plan/test procedure identifying the various stages of manufacture, quality checks performed at each stage, raw material inspection and the Customer hold points. The document shall also furnish details of method of checking, inspection and acceptance of standards/values and get the approval of Purchaser before proceeding with manufacturing. However, Purchaser shall have right to review the inspection reports, quality checks and results of suppliers in-house inspection department which are not Customer hold points and the supplier shall comply with the remarks made by purchaser or his representative on such reviews with regards to further testing, rectification or rejection, etc.
- **5.02** Witness and Hold points are critical steps in manufacturing, inspection and testing where the supplier is obliged to notify the Purchaser in advance so that it may be witnessed by the Purchaser. Final inspection is a mandatory hold point. The supplier is to proceed with the work past a hold point only after clearance by purchaser or a witness waiver letter from BYPL.
- **5.03** The performance of waiver of QA activity by Purchaser at any stage of manufacturing does not relieve the supplier of any obligation to perform in accordance with and meet all the requirements

- of the procurement documents and also all the codes & reference documents mentioned in the procurement document nor shall it preclude subsequent rejection by the purchaser.
- **5.04** On completion of manufacturing the items can only be dispatched after receipt of dispatch Instructions issued by the Purchaser.
- **5.05** All in-house testing and inspection shall be done without any extra cost. The in-house inspection shall be carried out in presence of BSES/BSES authorized third-party inspection agency. Cost of Futile/abortive visit(s) shall be debited from the invoices.
- **5.06** Purchaser reserves the right to send any material being supplied to any recognized laboratory for testing, wherever necessary and the cost of testing shall be borne by the Bidder. In case the material is found not in order with the technical requirement/specification, the charges along with any other penalty that may be levied are to be borne by the bidder.

6.0 Inspection & Test Charges

- 6.01 GOODS shall be inspected by BUYER and/or third-party inspection agency nominated by BUYER. Inspection shall carry out stage-wise/final inspection as per agreed QA /QC procedure. In addition, inspection of GOODS shall be carried out at our Site/stores. SELLER shall, however, repair/replace the damaged/rejected GOODS to the satisfaction of BUYER at no extra cost.
- 6.02 Inspection charges are included in total order value, however, BUYER will bear third-party inspection charges. In case of a futile/abortive visit of BUYER's inspector at SELLER'S works, the cost towards the same shall be debited from the SELLER's invoices.
- 6.03 GOODS covered by this PURCHASE ORDER shall not be dispatched in whole or in part until SELLER has received a written Release for Shipment Notice from BUYER or their designated representative.
- 6.04 Inspection call shall be raised a minimum of 7 (seven) days in advance from the delivery schedule mentioned in the PO and duly filled Format issued by BYPL

7.0 Handling and Storage

7.01 Material Safety Data Sheet (MSDS), detail handling & storage instruction sheet/manual, wherever applicable, to be furnished before the commencement of supply and one copy is to be submitted in store/site with First Lot.

8.0 Packing, Packing List & Marking

- 8.01 **Packing:** Supplier shall pack or shall cause to be packed all Commodities in crates/boxes/drums/containers/cartons and otherwise in such a manner as shall be reasonably suitable for shipment by road or rail to BYPL, Delhi/New Delhi stores/site without undue risk of damage in transit. All the packaging materials as prescribed shall be supplied preferably with bio-degradable packing- materials.
- 8.02 **Packing List:** The contents of each package shall be itemized on a detailed list showing the exact weight, extreme outside dimensions (length, width & weight) of each container/box/drum/carton, Item SAP Code, PO No & date. One copy of the packing list shall be enclosed in each package delivered.

GENERAL CONDITIONS OF CONTRACT(GCC) NIT NO: CMC/BY/24-25/RS/SkS/SV/09	Page 4 of 17	Bidders seal & Signature
[RFx Number: 2200000026]		

9.0 Prices/Rates/Taxes

9.01 **Price basis for supply of materials**

- a) Bidder to quote their prices on Landed Cost Basis and separate price for each item for supply to BYPL Delhi/New Delhi stores inclusive of packing, forwarding, loading at manufacturer's premises, payment of GST, Freight, and any other local charges. **Octroi is presently not applicable in Delhi and however if applicable shall be reimbursed at actuals.**
- b) The above supply prices shall also include unloading at BYPL Delhi/New Delhi stores/sites.
- c) Transit insurance will be arranged by Bidder

10.0 Taxes & Duties

- 10.01 Prices for Goods are on Ex- Works basis. For the Goods covered under the GST laws, all taxes that are applicable under CGST, SGST, UGST, IGST and GST Compensation Cess shall be payable extra.
- 10.02 For the Goods not covered in the GST laws, the applicable ED, VAT / CST shall be payable extra at applicable rates.
- 10.03 GSTIN of BSES YAMUNA POWER LTD 07AABCC8569N1Z0 CST No of BSES YAMUNA POWER LTD -07740254593 TIN NO of BSES YAMUNA POWER LTD 07740254593 PAN NO of BSES YAMUNA POWER LTD AABCC8569N
- 10.04 At the end of each month, the SELLER must submit their detail of invoices and amount thereof to the concerned officer in charge, within 07 days after the close of the respective month to which supply relates. Non-submission of the said request would be treated as good as the SELLER has no requirement for reconciliation.

11.0 Invoicing Instructions

- 11.01 Invoices in triplicate [1) Original for recipient, 2) Duplicate for Transporter, 3) Triplicate for supplier] shall be made out and delivered to the following address: BSES YAMUNA POWER LIMITED, SHAKTI KIRAN BUILDING, KARKARDOOMA, DELHI-110032.
 MDCC will be released separately for Capex & Opex. Invoice will be submitted by the supplier as per the MDCC.
- 11.02 Vendor shall obtain GST registration in the State from where the supply will be carried out. Vendors supplying Goods to the Purchaser shall have a valid GST registration number and shall submit GST Tax Invoice and other documents as per SGST Act, CGST Act, IGST Act, UTGST Act, GST Compensation Cess Act and Rules made there under. Failure to submit GST Tax Invoice shall be liable for withholding SGST, CGST, IGST, UTGST, GST Compensation Cess amount charged by the vendor while releasing the payment.
- 11.03 Invoice will be in the name of BSES YAMUNA POWER LIMITED & address of the store/site mentioned in the MDCC. Invoice should contain all information as required under GST Invoice, Debit Note and Credit Rules. The government has notified rules of invoicing under GST along with a template of invoice(GST INV-01) covering the elements such as supplier's details, GSTIN No, HSN Codes, item details, GST tax rates, etc that need to be presented by the supplier.
- 11.04 Vendor to carefully examine and charge relevant CGST / SGST, UGST, IGST and GST compensation cess as applicable to the transactions.

GENERAL CONDITIONS OF CONTRACT(GCC) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 5 of 17	Bidders seal & Signature
--	----------------------------	--------------------------

- 11.05 Timely provision of invoices / Debit Notes / Credit Notes:
- 11.05.1 Vendor to timely provide invoice / Debit note / Credit note to enable Purchaser to claim tax benefit on or before stipulated time period. All necessary adjustment entries (Credit Notes, Purchase Returns, Debit Notes) shall be made within the timelines prescribed under the GST Laws.
- 11.05.2 In case of receipt of advance, the Vendor undertakes to raise the tax invoice. Purchaser, upon payment of advance, shall issue payment voucher as per applicable GST laws and rules. Four copies of the invoices need to be provided by suppliers and wherever the law requires, an Electronic Reference Number for each invoice.

Documents and devices to be carried by a person in charge of a conveyance under.

- 11.05.3 Any Vendors / Contractors / Service providers 'shall' mention the following minimum requirements in 'invoice' while furnishing Invoices with us:
 - 1. Invoice / Credit Note Number and Date.
 - 2. Address of supplier/service provider and GSTN.
 - 3. Customer Name and Address as per GST Registration Certificate and GST registration Number.
 - 4. 'Shipped to' and 'Billed to' addresses.
 - 5. Place of Supply.
 - 6. Description of Goods/Service along with unit of measurements.
 - 7. HSN / SAC Code.
 - 8. Taxable value (Gross & deduct Discount separately if allowed)
 - 9. Rate and amount of Tax separately for CGST, SGST and IGST as applicable.
 - 10. Signature of Supplier. (For e-invoices physical signature is not required)
 - 11. Whether Reverse Charge is applicable or not.
- 11.06 E Way Bills/transit documents for movement of Goods:

Wherever applicable, the Vendor shall be responsible for issuing required transit documents / E Way Bills for the movement of Goods and the logistic partner/transporter shall not be liable for any loss arising due to confiscation of goods by government agencies on account of lack of proper documents or any misdeclaration. The Supplier is responsible for complying with rules applicable to the E-way bill. Any violation in provision of E-way Bill will attract penalties and seizure of Transit Material. Any Penalty and Pre-Deposit due to violation of rules/provisions shall be paid and borne by the Supplier. Also, the Supplier is responsible for releasing goods from the Authority whether CGST/SGST. Delay in supply from the contractual date due to the seizure of goods shall also attract liquidated damages.

12.0 Terms of Payment and Billing

12.01 For Supply of equipment/item:

100% payment shall be made within 45 days from the date of receipt & acceptance of material at store/site against submission of the following documents against dispatch of each consignment at our Vendor Support Cell (VSC):

- a) Signed copy of accepted Rate Contract (as applicable) & Purchase Order (for first payment)
- b) LR / RR / BL as applicable
- c) Challan as applicable
- d) Two (02) copies of the Supplier's detailed Recipient Invoice showing Commodity description, quantity, unit price, total price and basis of delivery, and is 100% of the value of the consignment claimed.
- e) Two (02) copies of Supplier's transporter invoice duly receipted by BYPL Store & Original certificate issued by BYPL confirming receipt of the subject material at Store/Site and acceptance of the same as per the provisions of the contract.
- f) Two (02) copies Packing List / Detailed Packing List

- g) Approved Test certificates / Quality certificates, if applicable
- h) Certificate of Origin, if applicable
- i) Material Dispatch Clearance Certificate (MDCC)
- j) Warranty / Guarantee Certificate, if applicable
- k) Checklist for bill submission.
- 12.02 Purchaser has the right to recover tax loss, interest and penalty suffered due to any non-compliance of tax laws by the Vendor. In the event, Purchaser is not able to avail of any tax credit due to any shortcoming on the part of the Vendor (which otherwise should have been available to Purchaser in the normal course), then the Vendor at his own cost and effort will get the short coming rectified. If for any reason the same is not possible, then the Vendor will make 'good' the loss suffered by Purchaser due to the tax credit it lost. In such event, any amount paid to the Vendors shall be first attributable to the tax (GST) charged in the invoice and the balance shall be considered towards the 'value' of supply of goods/ services.
- 12.03 Purchaser shall deduct "Tax Deducted at Source" wherever applicable and at the rate prescribed under the GST Laws or any other Indian law and remit the same to the Government. Necessary TDS certificates as per law shall be issued by the purchase to the vendor.
- 12.04 Any liability arising out of dispute on the tax rate, classification under HSN, calculation and payment of tax to the Government will be to the Vendor's account.
- 12.05 Where the supply of Goods is liable to GST under reverse charge mechanism, then the supplier should clearly mention the category under which it has been registered and also that "the liability of payment of GST is on the Recipient of Supply".

13.0 Tax Indemnity Clause

- 13.01 Vendor (along with its affiliates in India or overseas including any agent/ third party contractor or any other person appointed by such affiliates for this agreement) agrees that it will be solely responsible for performing all compliances and making payments of all taxes (direct tax or indirect tax including but not limited to income-tax, transfer pricing, value added tax, SGST, CGST, IGST, UTGST, GST Compensation Cess custom duty, excise duty, Research and Development Cess, etc.), cesses, interest, penalties or any other tax/ duty/ amount/ charge/ liability arising either out of laws/ regulations applicable in India and overseas or because of a demand/ recovery initiated by any revenue authority under laws/ regulations applicable in India or overseas.
- 13.02 In case any tax liability (including but not limited to income tax, transfer pricing, value added tax, SGST, CGST, IGST, UTGST, GST Compensation Cess, custom duty, excise duty, Research and Development Cess, etc.), cesses, interest, penalties or any other tax/ duty/ amount/ charge/ liability becomes payable by Purchaser due to failure of the Vendor, or any of its affiliates in India or overseas including any agent/ third party contractor or any other person appointed by such affiliates for this agreement, to comply with the relevant laws/ regulations applicable in India or overseas, Vendor undertakes to indemnify Purchaser for an amount equal to amount payable by Purchaser.
- 13.03 Further, Vendor undertakes to keep Purchaser indemnified at all times against and from all other actions, proceedings, claims, loss, damage, costs and expenses which may be brought against Purchaser or suffered or incurred by Purchaser and which shall have arisen either directly or indirectly out of or in connection with failure of The Vendor, or any of its affiliates in India or overseas including any agent/ third party contractor or any other person appointed by such affiliates for this agreement, to comply with relevant obligations/ compliance under any law/ regulations applicable in India and overseas.

GENERAL CONDITIONS OF CONTRACT(GCC)
NIT NO: CMC/BY/24-25/RS/SkS/SV/09
[RFx Number: 2200000026]

- 13.04 The parties agree to follow the following process in case any communication of demand, arising out of non-compliance by Vendor (along with its affiliates in India or overseas including any agent/third party contractor or any other person appointed by such affiliates for this agreement), is received by Purchaser:
- 13.04.1 On Purchaser receiving any communication from a competent authority demanding tax liability (including but not limited to income tax, transfer pricing, value added tax, SGST, CGST, IGST, UTGST, GST Compensation Cess custom duty, excise duty, Research and Development Cess, etc.), cesses, interest, penalties or any other tax/ duty/ amount/ charge/ liability, Purchaser shall, within 5 common working days from the date of receipt of such communication (save where the period to respond to the relevant authority is less than five days, in which case, as soon as reasonably possible) inform Vendor in writing of such communication.
- 13.04.2 Pursuant to receiving communication from Purchaser, Vendor shall suggest to accept the communication and pay the demand amount to the competent authority. In such an event, Vendor shall reimburse such amount paid to Purchaser within 5 working days from the date of payment by Purchaser to the competent authority.
- 13.04.3 If Vendor advises in writing and Purchaser agrees to dispute the demand, then Purchaser shall dispute the matter with competent authority as per due process prescribed under the regulations and Purchaser shall not pay the Tax Demand. In such scenario, cost of litigation including but not limited to Counsel cost, filing fees, other related charges, should be reimbursed by Vendor to Purchaser. Additionally, If any coercive steps of recovery are initiated by the department, then Purchaser would pay such amount (including by way of adjustment of refunds due to it) and the same would be reimbursed by Vendor within 5 working days from date of such recovery from Purchaser. Purchaser will take all necessary steps to avoid such recovery measures.
- 13.04.4 On determination of the demand through an Order issued by a Tribunal or any other similar Authority, by whatever name called, under any law applicable in India or overseas, if the demand or any part thereof becomes payable and is paid by Purchaser, then Vendor undertakes to reimburse such amount to Purchaser within 10 days from the date of payment. Alternatively, if on determination of the demand through an Order, no amount is payable by Purchaser then any refund arising to Purchaser due to such an Order shall be passed on to Vendor within 10 days from the date of receipt of refund.

14.0 The Micro, Small and Medium Enterprises (MSME)

14.01 If the SELLERS establishment is covered under the purview of The Micro, Small and Medium Enterprises Development Act, 2006 and its amendments, he shall declare so within the bid of its status failing which it will be presumed that it is a non-MSME unit. Also, submit a copy of Udyog Aadhaar (UA) & Udyam Registration Number.

15.0 Price Validity

15.01 All bids submitted shall remain valid, firm and subject to unconditional acceptance by BYPL Delhi for 120 days from the due date of submission. For awarded suppliers, the prices shall remain valid till contract completion.

16.0 Performance Guarantee

16.01 To be submitted within twenty-eight (28) days from the date of issuance of the Letter of Intent/Award/PO. Bidder shall submit the performance bank guarantee (PBG) equivalent to 10%

- of the PO value (including GST) valid for a period of 30 months from the date of last receipts at site/stores plus 3 months claim period.
- 16.02 Bank guarantee shall be drawn in favour of BSES Yamuna Power Ltd as applicable. The performance Bank guarantee shall be in the format specified by BYPL.

17.0 Forfeiture

- 17.01 Each Performance Bond established under Clause 10.0 shall contain a statement that it shall be automatically and unconditionally forfeited without recourse and payable against the presentation by BYPL of this Performance Bond, to the relevant bank referred to above, together with a simple statement that supplier has failed to comply with any term or condition outlined in the Contract.
- 17.02 Each Performance BG established under will be automatically and unconditionally forfeited without recourse if BYPL in its sole discretion determines that supplier has failed to comply with any term or condition outlined in the contract.

18.0 Release

18.01 All Performance Bonds will be released without interest within seven (7) days from the last date up to which the Performance Bond has to be kept valid (as defined in Clause 16.0) except for the case outlined in Clause 22.0.

19.0 Defects Liability Period/Guarantee/Warranty

- 19.01 The bidder is to Guarantee the materials/items supplied against any defect or failure, which arises due to faulty materials, workmanship or design for the entire defects liability period. The Defect liability period shall be 66 months from the date of receipt of each unit at store(s)/site(s).
- 19.02 If during the Defects Liability Period, any GOODS are found to be defective, they shall be promptly replaced or rectified by BIDDER at its own cost (including the cost of dismantling and (reinstallation) on the instructions of BUYER and if removed from SITE for such purpose, shall be removed and re-delivered to SITE by BIDDER at its own cost.

20.0 Return, Replacement or Substitution

20.01 BYPL shall give Supplier notice of any defective Commodity promptly after becoming aware thereof. BYPL may at its discretion elect to return defective Commodities to Supplier for replacement, free of charge to BYPL or may reject such Commodities and purchase the same or similar Commodities from any third party. In the latter case, BYPL shall furnish proof to Supplier of the cost of such substitute purchase. In either case, all costs of any replacement, substitution, shipping, labour and other related expenses incurred in connection with the return and replacement or for the substitute purchase of a Commodity hereunder should be for the account of Supplier. BYPL may set off such costs against any amounts payable by BYPL to the Supplier. Supplier shall reimburse BYPL for the amount, if any, by which the price of a substitute Commodity exceeds the price for such Commodity as quoted in the Bid. BUYER at its sole discretion shall have the opinion to dispose of the material or GOODS so rejected and not taken back within forty-five days from the date of intimation of rejection.

21.0 Effective Date of Commencement of Contract

GENERAL CONDITIONS OF CONTRACT(GCC)	Page 9 of 17	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		_
[RFx Number: 2200000026]		

21.01 The date of the issuance of the Letter of Acceptance/Purchase Order shall be treated as the effective date of the commencement of Contract.

22.0 Time – The Essence Of Contract

22.01 The time and the date of completion of the "Supply" as stipulated in the Letter Of Acceptance / Purchase order issued to the Supplier shall be deemed to be the essence of the "Contract". The Supply has to be completed not later than the aforesaid Schedule and date of completion of supply.

23.0 The Laws and Jurisdiction of Contract:

- 23.01 The laws applicable to this Contract shall be the Laws in force in India.
- 23.02 All disputes arising in connection with the present Contract shall be settled amicably by mutual consultation failing which shall be finally settled as per the rules of Arbitration and Conciliation Act, 1996 at the discretion of Purchaser. The venue of arbitration shall be Delhi, India

24.0 Events of Default

- 24.01 Events of Default. Each of the following events or occurrences shall constitute an event of default ("Event of Default") under the Contract:
 - (a) Supplier fails or refuses to pay any amounts due under the Contract;
 - (b) Supplier fails or refuses to deliver Commodities conforming to this RFQ/specifications, or fails to deliver Commodities within the period specified in P.O. or any extension thereof
 - (c) Supplier becomes insolvent or unable to pay its debts when due, or commits any act of bankruptcy, such as filing any petition in any bankruptcy, winding-up or reorganization proceeding, or acknowledges in writing its insolvency or inability to pay its debts; or the Supplier's creditors file any petition relating to bankruptcy of Supplier;
 - (d) Supplier otherwise fails or refuses to perform or observe any term or condition of the Contract and such failure is not remediable or, if remediable, continues for a period of 30 days after receipt by the Supplier of notice of such failure from BYPL.

25.0 Consequences of Default.

- (a) If an Event of Default shall occur and be continuing, BYPL may forthwith terminate the Contract by written notice.
- (b) In the event of an Event of Default, BYPL may, without prejudice to any other right granted to it by law, or the Contract, take any or all of the following actions;
 - (i) present for payment to the relevant bank the Performance Bond;
 - (ii) purchase the same or similar Commodities from any third party; and/or
 - (iii) recover any losses and/or additional expenses BYPL may incur as a result of Supplier's default.

GENERAL CONDITIONS OF CONTRACT(GCC) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026] Page 10 of 17	Bidders seal & Signature
---	--------------------------

26.0 Penalty for Delay

- 26.01 If supply of items/equipments is delayed beyond the supply schedule as stipulated in the purchase order then the Supplier shall be liable to pay to the Purchaser as penalty for delay, a sum of 1% (one percent) of the basic (ex-works) price for every week delay of undelivered units or part thereof for individual milestone deliveries.
- 26.02 The total amount of penalty for delay under the contract will be subject to a maximum of ten percent (10%) of the basic (ex-works) price of total undelivered units.
- 26.03 The Purchaser may, without prejudice to any method of recovery, deduct the amount for such damages from any amount due or which may become due to the Supplier or from the Performance Bond or file a claim against the supplier.
- 26.4 If the Penalty is levied as per the Order terms & conditions; BYPL will raise the Invoice for the penalty amount along with applicable GST rates. Accordingly, after setting off the penalty Invoice amount, net payment shall be made.

27.0 Variation in Taxes, Duties & Levies

- 27.1 The total order value shall be adjusted on account of any variations in Statutory Levies imposed by Competent Authorities by way of fresh notification(s) within the stipulated delivery period only. In case of reduction in taxes, duties and levies, the benefits of the same shall be passed on to BUYER.
- 27.2 No other Taxes, Duties or levies other than those specified above will be payable by BUYER except in case of new Levies, Taxes or duties imposed by the Competent Authorities by way of fresh notification(s) after the issue of PURCHASE ORDER but within the stipulated delivery period.
- 27.3 Notwithstanding what has been stated above, changes in Taxes, Duties & Levies shall apply only to that portion of PURCHASE ORDER not executed on the date of notification by the Competent Authority. Further, changes in Taxes, Duties & Levies after the due date of Delivery shall not affect PURCHASE ORDER Terms and Value.
- 27.4 PURCHASE ORDER value shall not be subject to any variation on account of variation in Exchange rate(s).

28.0 Taxes & Duties on raw materials & bought out components

- 28.01 Taxes & Duties on raw materials & bought-out components are included in Order Value and are not subject to any escalation or variation for any reason whatsoever.
- 28.02 Taxes & Duties on raw materials & bought-out components procured indigenously are included in Order Value and are not subject to any escalation or variation for any reason whatsoever.

29.0 Force Majeure

29.01 General

An "Event of Force Majeure" shall mean any event or circumstance not within the reasonable control directly or indirectly, of the Party affected, but only if and to the extent that:

(i) Such event or circumstance materially and adversely affects the ability of the affected Party to perform its obligations under this Contract, and the affected Party has taken all reasonable

GENERAL CONDITIONS OF CONTRACT(GCC) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 11 of 17	Bidders seal & Signature
--	-----------------------------	--------------------------

- precautions, due care and reasonable alternative measures to prevent or avoid the effect of such event on the affected party's ability to perform its obligations under this Contract and to mitigate the consequences thereof.
- (ii) For the avoidance of doubt, if such event or circumstance would not have materially and adversely affected the performance of the affected party had such affected party followed good industry practice, such event or circumstance shall not constitute force majeure.
- (iii) Such event is not the direct or indirect result of the failure of such Party to perform any of its obligations under this Contract.
- (iv) Such Party has given the other Party prompt notice describing such events, the effect thereof and the actions being taken to comply with the above clause.
- 29.02 Specific Events of Force Majeure subject to the provisions of above clause, Events of Force Majeure shall include only the following to the extent that they or their consequences satisfy the above requirements:
 - (i) The following events and circumstances:
 - a) Effect of any natural element or other acts of God, including but not limited to storm, flood, earthquake, lightning, cyclone, landslides or other natural disasters.
 - b) Explosions or fires
 - (ii) War declared by the Government of India.
 - (iii) Dangers of navigation, perils of the sea.
 - Note: Causes like power breakdowns/strikes, accidents etc do not fall under Force Majeure.
- 29.03 Notice of Events of Force Majeure If a force majeure event prevents a party from performing any obligations under the Contract in part or in full, that party shall:
 - i) Immediately notify the other party in writing of the force majeure events within 7(seven) working days of the occurrence of the force majeure event
 - ii) Be entitled to suspend performance of the obligation under the Contract which is affected by force majeure event for the duration of the force majeure event.
 - iii) Use all reasonable efforts to resume full performance of the obligation as soon as practicable
 - iv) Keep the other party informed of all such efforts to resume full performance of the obligation on a regular basis.
 - v) Provide prompt notice of the resumption of full performance or obligation to the other party.
- 29.04 Mitigation of Events of Force Majeure Each Party shall:
 - (i) Make all reasonable efforts to prevent and reduce to a minimum and mitigate the effect of any delay occasioned by an Event of Force Majeure including recourse to alternate methods of satisfying its obligations under the Contract;
 - (ii) Use its best efforts to ensure resumption of normal performance after the termination of any Event of Force Majeure and shall perform its obligations to the maximum extent practicable as agreed between the Parties; and
 - (iii) Keep the other Party informed at regular intervals of the circumstances concerning the event of Force Majeure, with best estimates as to its likely continuation and what measures or contingency planning it is taking to mitigate and or terminate the Event of Force Majeure.
- 29.05 Burden of Proof In the event that the Parties are unable in good faith to agree that a Force Majeure event has occurred to an affected party, the Parties shall resolve their dispute in accordance with the provisions of this Agreement. The burden of proof as to whether or not a force majeure event has occurred shall be upon the party claiming that the force majeure event has occurred and that it is the affected party.
- 29.06 Termination for Certain Events of Force Majeure. If any obligation of any Party under the Contract is or is reasonably expected to be delayed or prevented by a Force Majeure event for a continuous period of more than 3 months, the Parties shall promptly discuss in good faith how to proceed with

GENERAL CONDITIONS OF CONTRACT(GCC) NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	Page 12 of 17	Bidders seal & Signature
--	-----------------------------	--------------------------

a view to reaching a solution on mutually agreed basis. If a solution on mutually agreed basis cannot be arrived at within a period of 30 days after the expiry of the period of three months, the Contract shall be terminated after the said period of 30 days and neither Party shall be liable to the other for any consequences arising on account of such termination.

The Purchaser may terminate the contract after giving 7 (seven) days' notice if any of the following occurs:

- Bidder fails to complete the execution of works within the approved schedule of works, terms and conditions.
- ii. In case the Bidder commits any Act of Insolvency, or is adjudged insolvent
- iii. Has abandoned the contract
- iv. Has failed to commence work or has suspended the progress of works
- v. Has failed to proceed with the works with due diligence and failed to make such due progress
- 29.07 Limitation of Force Majeure event. The Supplier shall not be relieved of any obligation under the Contract solely because the cost of performance is increased, whether as a consequence of adverse economic consequences or otherwise.
- 29.08 Extension of Contract Period due to Force Majeure event The Contract period may be extended by mutual agreement of Parties by way of an adjustment on account of any period during which an obligation of either Party is suspended due to a Force Majeure event.
- 29.09 Effect of Events of Force Majeure. Except as otherwise provided herein or may further be agreed between the Parties, either Party shall be excused from performance and neither Party shall be construed to be in default in respect of any obligations hereunder, for so long as the failure to perform such obligations shall be due to an event of Force Majeure."
- 29.10 Severability
 - If any provision of this Agreement is or becomes invalid or unenforceable by the courts of any jurisdiction to which it is subject, such invalidity or unenforceability shall not prejudice the remaining provisions of this Agreement, which shall continue in full force and effect.

30.0 Transfer and Sub-Letting

30.01 The Supplier shall not sublet, transfer, assign or otherwise part with the Contract or any part thereof, either directly or indirectly, without prior written permission of the Purchaser.

31.0 Recoveries

31.01 Whenever under this contract any money is recoverable from and payable by the bidder, the purchaser shall be entitled to recover such sum by appropriating in part or in whole by detecting any sum due to which any time thereafter may become due from the supplier in this or any other contract. Should the sum be not sufficient to cover the full amount recoverable the bidder shall pay to the purchaser on demand the remaining balance.

32.0 Waiver

32.01 Failure to enforce any condition herein contained shall not operate as a waiver of the condition itself or any subsequent breach thereof.

33.0 Indemnification

33.01 Notwithstanding contrary to anything contained in this RFQ, Supplier shall at his costs and risks make good any loss or damage to the property of the Purchaser and/or the other Supplier engaged by the Purchaser and/or the employees of the Purchaser and/or employees of the other Supplier engaged by the Purchaser whatsoever arising out of the negligence of the Supplier while performing the obligations under this contract.

34.00 Termination for convenience of Purchaser

- Purchaser at its sole discretion may terminate the contract by giving 30 days prior notice in writing or through email to the Supplier. Purchaser shall pay the Supplier for all the supplies/ services rendered till the actual date of contract termination against submission of invoice by the Supplier to that effect.
- Payment of such compensation is the sole and exclusive remedy of the supplier for termination of this Agreement by Purchaser hereunder and the supplier shall not be entitled to, and hereby waives, claims for lost profits and all other damages and expenses.
- 34.3 Supplier hereby agrees that substantiation for settlement of any claims submitted by supplier shall be complete and in sufficient detail to allow Purchaser's evaluation. Terminate all sub-contracts except those that have been/ to be assigned to the Purchaser all rights, titles and benefits of the Suppliers/Vendor as the case may be.

35.00 Documentation

35.01 The Bidder shall procure all equipment from BYPL-approved sources as per the attached specifications. The Bidders shall submit copies of Material/Type Test Certificates, O&M Manuals, and Approved & As-built drawings, related to various equipment (as applicable). The Bidder shall ensure strict compliance with the specifications and Field Quality Procedures issued by BYPL.

36.0 Transit Insurance

- 36.01 Transit Insurance shall be arranged by the Bidder.
- 36.02 DAMAGE / LOSS OF CARGO IN TRANSIT: The vendor shall be solely responsible for coordinating with the concerned insurance company for procuring insurance for material and/or Goods, processing claims lodgment and settlement. Notwithstanding the insurance cover, in case of loss/damage to material and/or Goods, in any manner and for any cause whatsoever, Vendor shall cause the damaged cargo to be replaced and delivered to the Purchaser with new material and/or Goods within 30 days of such loss/damage. The Vendor shall be solely responsible for all expenses in relation to the replacement and delivery in such circumstances.

37.0 Limitation of Liability

- **37.01** Except for willful misconduct or gross negligence, neither Party shall be liable to the other Party for loss of use of any Works, loss of profit, loss of any contract or any other indirect or consequential loss or damage which may be suffered by the other Party in connection with the Contract. The total liability of the Supplier to the Purchaser under the Contract shall not exceed the Contract Value. Except that this Clause shall not limit the liability of the Supplier:
 - (a) In cases of fraud, willful misconduct or illegal or unlawful acts, or
 - (b) In cases of acts or omissions of the Supplier that are contrary to the most elementary rules of diligence that a conscientious Supplier would have followed in similar circumstances.

38.0 Liability of Suppliers

38.1 Subject to the due discharge of its obligations under the Contract and except in case of gross negligence or willful misconduct on the part of the Supplier or on the part of any person acting on behalf of the Supplier, with respect to any loss or damage caused by the Supplier to the Purchaser's property or the Site, the Supplier shall not be liable to the Purchaser for the following:

		_	
GENERAL CONDITIONS OF CONTRACT(GCC) NIT NO: CMC/BY/24-25/RS/SkS/SV/09	Page 14 of 17	Bidders seal & Signature	
[RFx Number: 2200000026]			

- (a) For any indirect or consequential loss or damage; and
- (b) For any direct loss or damage that exceeds:
- (i) The total payments made and expected to be made to the Supplier under the Contract including reimbursements, if any; or
- (ii) The insurance claim proceeds that the Supplier may be entitled to receive from any insurance purchased by the Supplier to cover such a liability, whichever is higher.
- This limitation of liability shall not affect the supplier's liability, if any, for damage to third-party property or injury or death of a person due to negligence of the Contractor or any Person or firm acting on behalf of the supplier in executing the order.
- 38.3 Notwithstanding anything contained in the Contract, the Supplier shall not be liable for any gross negligence or willful misconduct on the part of the Purchaser or any of its affiliates, any vendor, or any party, other than Supplier and/or, its directors, officers, agents or representatives or its affiliates, or SubSupplier, or the vendor or any third party engaged by it.
- Notwithstanding anything contained in the Contract, including but not limited to approval by the Purchaser of any drawings, documents, vendor list, supply of information or data or the participation of the Purchaser in any meeting and/or discussion or otherwise, shall not absolve the Supplier from any of its liabilities or responsibilities arising in relation to or under the Contract.

39.0 Intellectual Property Rights and Royalties

- The Supplier shall indemnify the Purchaser and the Purchaser's Representative from and against all claims and proceedings on account of infringement (or alleged infringement) of any patent rights, registered designs, copyright, design, trademark, trade name, know-how or other intellectual property rights (hereinafter collectively referred to as "Intellectual Property Rights") in respect of the Works, Supplier's Equipment, machines, Works method, Plant, Materials, or anything whatsoever required for the execution of the Works and from and against all claims, demands, proceedings, damages, costs, charges and expenses whatsoever in respect thereof or in relation thereto. In the event of an infringement of any Intellectual Property Rights of any third party as a result of the execution of the Works (or any part thereof) by the Supplier, the Supplier shall rectify, modify or replace, at its own cost, the Works, Plant or Materials or anything whatsoever required for the Works so that infringement ceases to exist or, in the alternative, the Supplier shall procure necessary rights/ licenses from the affected third party so that there is no infringement of Intellectual Property Rights.
- 39.2 The Supplier shall be promptly notified of any claim made against the Purchaser. The Supplier shall, at its cost, conduct negotiations for the settlement of such claim, and any litigation or arbitration that may arise from it. The Purchaser or the Purchaser's Representative shall not make any admission that might be prejudicial to the Supplier unless the Supplier has failed to take over the conduct of the negotiations, litigation or arbitration within a reasonable time after having been so requested. In the event of the Supplier failing to act at the Purchaser's Representative's notice, the Purchaser shall be at full liberty to deduct any such amount of pending claim from any amount due to the Supplier under the Contract or any other contract and the balance portion of claim shall be treated as debt due from the Supplier.
- 39.3 All Intellectual Property Rights in respect of any Plant, Materials, Drawings and Designs, plans, documents, specifications, data, materials, know-how, charts, information, etc., provided to the Supplier by the Purchaser pursuant to this Contract for the execution of the Works, belongs to and shall continue to belong to the Purchaser and the Supplier shall not have any rights in the same other than the limited right for its use for the purpose of execution of the Works.
- 39.4 Intellectual Property Rights in respect of any Plant, Materials, Drawings and Designs, plans,

		1
GENERAL CONDITIONS OF CONTRACT(GCC)	Page 15 of 17	Bidders seal & Signature
	90 =0 0. =1	8
NIT NO: CMC/BY/24-25/RS/SkS/SV/09		
[RFx Number: 2200000026]		
[KLX Nulliber: 2200000020]		

- calculations, drawings, documents, know-how and information relating to the Works which are proprietary to the Supplier and/ or its third-party licensors ("**Supplier's IPR**") shall continue to vest with the Supplier and/ or its third-party licensors and the Supplier shall grant and/ or procure from its third party licensors, at its own cost, a worldwide, perpetual, royalty-free, non-exclusive license (along with the right to sub-license) to use and reproduce such Supplier's IPR for the use, operation, maintenance and repair of the Works.
- 39.5 If any patent, trademark, trade name, registered design or software is developed by the Supplier or its SubSupplier specifically for the execution of the Works, then all Intellectual Property Rights in respect of such design, trademark, trade name or software shall be the absolute property of the Purchaser and shall not be utilized or retained by the Supplier (or its SubSuppliers) for any purpose other than with the prior written consent of the Purchaser.
- 39.6 If the Supplier uses proprietary software (whether customized or off the shelf) for the purpose of storing or utilizing records in relation to the Works, the Supplier shall obtain at its own expense, the grant of a worldwide, royalty-free, perpetual licence or sublicence (including the right to sublicense) to use such software, in favour of the Purchaser provided that the use of such software under the licence or the sublicense may be restricted to use any such software only for the design, construction, reconstruction, manufacture, installation, completion, reinstallation, repair and operation of the Works or any part thereof.
- 39.7 If any software is used by the Supplier for the execution of the Works over which the Supplier or a third party holds pre-existing title or other rights, the Supplier shall obtain for the Purchaser, a worldwide, royalty-free, perpetual license for the right to use and apply that software (together with any modifications, improvements and developments thereof).

40.0 Acceptance

- 40.01 Vendor confirms to have gone through the Policy of BYPL on legal and ethical code required to be followed by vendors encapsulated in the "Vendor Code of Conduct" displayed on the official website of BYPL (www.bsesdelhi.com) also, which shall be treated as a part of the contract/PO/WO. The vendor undertakes that he shall adhere to the Vendor Code of Conduct and also agrees that any violation of the Vendor Code of Conduct shall be treated as breach of the contract/PO/WO. In the event of any such breach, irrespective of whether it causes any loss/damage, Purchaser (BYPL) shall have the right to recover loss/damage from Vendor. The Contractor/Vendor hereby indemnifies and agrees to keep indemnified the Purchaser (BYPL) against any claim/litigation arising out of any violation of Vendor Code of Conduct by the Contractor/Vendor or its officers, agents & representatives etc.
- 40.02 Acceptance of the CONTRACT implies and includes acceptance of all terms and conditions enumerated in the CONTRACT in the technical specification and drawings made available to Contractor consisting of general conditions, detailed scope of work, detailed technical specification, detailed equipment drawing and complete scope of work.
- 40.03 Contractor and Company contractual obligations are strictly limited to the terms set out in the CONTRACT. No amendments to the concluded CONTRACT shall be binding unless agreed to in writing for such amendment by both parties.
- 40.04 We expect your services and supplies to be aligned to our Vision, Mission and Values. Please refer to the following link to know about our Vision, Mission and Values; https://www.bsesdelhi.com/web/bypl/about-bses.


GENERAL CONDITIONS OF CONTRACT(GCC)	Page 16 of 17	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]		

QUANTITY AND DELIVERY REQUIREMENTS

SI. No.	BYPL SAP Code	Item Description	Specificati on	Total Qty. (Nos)	Tentative Delivery Schedule	Destination
1	2100268104	SUPPLY OF SINGLE PHASE NATURAL ORGANIC ESTER OIL FILLED COMPLETELY SELF PROTECTED (CSP) TRANSFORMER OF RATING 25KVA 6.35/0.240kV	BSES-TS- 30-SPT-R0	350	Delivery shall be commencing within 02 Month from the PO and completion @100 Nos per month	BYPL Delhi Store(s)/ Site(s)

The delivery schedule shown above is tentative. PO(s) will be released as per the actual requirement. However, the supplier has to deliver the material within the delivery schedule provided.

Schemes may be executed in a phased manner.



APPENDIX II

<u>ANNEXURE - 2.01</u>

FORMAT OF PERFORMANCE BANK GUARANTEE (To be executed on a Non-Judicial Stamp Paper of appropriate value)

This Gu	uarantee made at this [] c	day of [] 20XX				
1.	WHEREAS M/s BSES Yamuna Power Companies Act, 1956 having its Register India hereinafter referred to as the "context or meaning thereof include its	ered Office at Shaktikiran Owner ", (which expres	Building, Karkardoa, Delhi 110032, ssion shall unless repugnant to the			
2.	AND WHEREAS the Owner has entered of contract here) vide Contract No the "Contract") with M/s expression shall unless repugnant to include each of their respective successconditions as more particularly detailed		(hereinafter referred to as ferred to as "the Supplier", which thereof be deemed to mean and			
3.	AND WHEREAS as per clauseof to the Owners an unconditional bank g the total Contract Value for the time! Contract from [] pl. at [] through its brank B.G is issued) hereinafter referred to a to the context or meaning thereof be context.	guarantee for an amount ly completion and faithf specify the name of Bannach in(pl. specify as "the Bank", (which exp	equivalent to ten percent (10%) of ful and successful execution of the pk) having its head/registered office of the name of Branch through which pression shall unless it be repugnant			
4.	NOW THEREFORE, in consideration inter alia of the Owner granting the Suppliers the Contract, the Bank hereby unconditionally and irrevocably guarantees and undertakes, on a written demand, to immediately pay to the Owner any amount so demanded (by way of one or more claims) not exceeding in the aggregate [Rs.]					
5.	The decision of the Owner to invoke performed its obligations under the Cor		• •			
NIT N	APPENDIX II Page 1 of 6 Bidders seal & Signature NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]					

that any such demand by the Owner of the amounts payable by the Bank to the Owner shall be final, binding and conclusive evidence in respect of the amounts payable by the Supplier to the Owner. Any such demand made by the Owner on the Bank shall be conclusive and binding, notwithstanding any difference between the Owner and the Supplier or any dispute raised, invoked, threatened or pending before any court, tribunal, arbitrator or any other authority.

- 6. The Bank also agrees that the Owner at its option shall be entitled to enforce this Guarantee against the Bank as a principal debtor without proceeding against the Suppliers notwithstanding any other security or other guarantee that the Owner may have in relation to the Supplier's liabilities.
- 7. The Bank hereby waives the necessity for the Owner first demanding the aforesaid amounts or any part thereof from the Suppliers before making payment to the Owner and further also waives any right the Bank may have of first requiring the Owner to use its legal remedies against the Suppliers, before presenting any written demand to the Bank for payment under this Guarantee.
- 8. The Bank's obligations under this Guarantee shall not be reduced by reason of any partial performance of the Contract. The Bank's obligations shall not be reduced by any failure by the Owner to timely pay or perform any of its obligations under the Contract.
- 9. The Bank further unconditionally and unequivocally agrees with the Owner that the Owner shall be at liberty, without the Bank's consent and without affecting in any manner its rights and the Bank's obligation under this Guarantee, from time to time, to:
 - (i) vary and/or modify any of the terms and conditions of the Contract;
 - (ii) Forebear or enforce any of the rights exercisable by the Owner against the Suppliers under the terms and conditions of the Contract; or
 - (iii) Extend and/or postpone the time for performance of the obligations of the Suppliers under the Contract;

and the Bank shall not be relieved from its liability by reason of any such act or omission on the part of the Owner or any indulgence shown by the Owner to the Suppliers or any other reason whatsoever which under the law relating to sureties would, but for this provision, have the effect of relieving the Bank of its obligations under this Guarantee.

10. This Guarantee shall be a continuing bank guarantee and shall not be discharged by any change in the constitution or composition of the Suppliers, and this Guarantee shall not be affected or

APPENDIX II	Page 2 of 6	Bidders seal & Signature
NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]	-	-

	the Suppliers or any of them or any other circumstances whatsoever.
11.	This Guarantee shall be in addition to and not in substitution or in derogation of any other security
	held by the Owner to secure the performance of the obligations of the Suppliers under the Contract.
12.	NOTWITHSTANDING anything herein above contained, the liability of the BANK under this
	Guarantee shall be restricted to(insert an amount equal to ten percent
	(10%) of the Contract Value) and this Guarantee shall be valid and enforceable and expire on
	(pl. specify date) or unless a suit or action to enforce a claim under this Guarantee
	is filed against the Bank on or before the date of expiry.
13.	On termination of this Guarantee, all rights under the said Guarantee shall be forfeited and the
	Bank shall be relieved and discharged from all liabilities hereunder.
14.	The Bank undertakes not to revoke this Guarantee during its validity except with the prior written
	consent of the Owner and agrees that any change in the constitution of the Bank or the Suppliers
	shall not discharge our liability hereunder.
15.	This Guarantee shall be governed by the laws of India. Any suit, action, or other proceeding arising
	out of, connected with, or related to this Guarantee or the subject matter hereof shall be subject
	to the exclusive jurisdiction of the courts of Delhi , India.
	Dated this day of
4	(Signature)
	(1)
	(Name)
	(Designation with Bank Stamp)
	Attorney as per Power of Attorney No
	Date

discharged by the liquidation, winding-up, bankruptcy, reorganization, dissolution or insolvency of

APPENDIX II NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026]

ANNEXURE - 2.02

BYPL BANK DETAIL WITH IFSC CODE:

1. Name of the Bank: Axis Bank Limited

2. Branch Name & Full Address: C-58, Basement & Ground Floor, Preet Vihar, Main Vikas Marg,

New Delhi 110092

3. Branch Code: 055

4. Bank Account No: 911030003596085

5. IFSC Code: UTIB0000055

6. Swift Code: AXISINBB055

ANNEXURE - 2.03

FORMAT OF WARRANTY/GUARANTEE CERTIFICATE

BSES YAMUNA POWER LIMITED Shaktikiran Building, Karkardooma, Delhi -110032.

Ref. Purchase Order No.:

Dear Sir,

We hereby confirm that the......dispatched to BSES YAMUNA POWER LTD vide invoice no.......

DT.....is exactly of the same nature and description as per above mentioned Purchase Order.

We further confirm that we will replace/repair our......free of cost if any manufacturing defect

during.....months from the date of dispatch of material or.....months from the date of commissioning

whichever is earlier.

Vendor Name & Signature

ANNEXURE - 2.04

UNDERTAKING GST

The Vendor shall give an undertaking in the following words on each invoice in the absence of which tax payment as on the Vendor's invoice may be withheld.

"The tax component as mentioned in the invoice shall be deposited with the GST Department as per law by way of actual payment or by way of legal set off as per law. The turnover billed shall be duly declared in my GST returns a copy of which shall be filed with the Purchaser. Should the input tax credit to the Purchaser be denied by way of any lapse on the part of the Vendor, the same shall be paid on demand and in any case the Purchaser is authorized to deduct the tax equivalent amount from the amount payable to the Vendor"

APPENDIX II NIT NO: CMC/BY/24-25/RS/SkS/SV/09 [RFx Number: 2200000026] Page **5** of **6**

Bidders seal & Signature

ANNEXURE – 2.05 SUMMARY OF COMMERCIAL TERMS AND CONDITIONS - SUPPLY


	SUMMARY OF COMMERCIAL TERMS AND CONDITIONS - SUPPLY				
SL NO	PARTICULARS	CLAUSE AS PER TENDER	BIDDER'S CONFIRMATION		
1	Validity	120 days from the date of submission of the bid			
2	Price basis	"Firm", FOR Delhi store(s)/site(s) basis. Prices shall be inclusive of all taxes & duties, freight up to Delhi store(s)/site(s).			
3	Unloading	Unloading at stores/sites shall be in vendor's scope			
4	Transit insurance	Transit insurance in Bidder's scope			
5	Payment terms	100% payment shall be paid within 45 days from the date of receipt and acceptance of GOODS at store/site against submission of documents.			
6	Delivery Schedule	Transmittal Approval Documents (GTP/Drawings/QAP/etc.) are to be submitted within 15 days to the concerned official in BYPL for approval. BYPL shall approve/provide comments on the submitted drawings within 7 days of first submission. In case resubmission is required, it shall be completed by the supplier within next 5 days. The timelines for approval by BYPL shall be 5 days in case of every resubmission. However, repetitive submissions are not desirable. Delivery shall be commencing within 02 Month from the PO and completion @100 Nos per month.			
7	Defect Liability Period	Defect Liability 66 months from the date of receipt of each unit at			
8	Penalty for delay	1% (One) of the basic value (ex-works value) of undelivered			
9		To be submitted within twenty-eight (28) days from the date of issuance of the Letter of Intent/Award/RC. Bidder shall initially submit the performance bank guarantee (PBG) equivalent to 10% of the PO value (including GST) valid for a period of 30 months from the date of last receipts at site/stores plus 3 months claim period.			
		Acceptance for participation in Reverse Auction event			
	the Diddow				

Saal	of the	Ridder

				_			
ci	~	-	-	٠.	٠	r۵	

Name:

APPENDIX II NIT NO: CMC/BY/24-25/RS/SkS/SV/09	Page 6 of 6	Bidders seal & Signature
[RFx Number: 2200000026]		



PRICE BID FORMAT
NIT NO: CMC/BY/24-25/RS/SkS/SV/09
[RFx Number: 2200000026]

Page 1 of 2

Bidders seal & Signature

ALL PRICES IN INR (₹)

									21117
				QTY	UNIT	UN	IT GST &	UNIT	TOTAL
					BASIC	C	ESS AS	LANDED	LANDED
		HSN			PRICE	APF	PLICABLE	RATE	VALUE (₹)
S.		CODE			INCL		CGST &	(All	
No.	DESCRIPTION OF GOODS	(8 Digit	UoM		FREIGHT	SGST	/UTGST or	Inclusive)	
NO.		Mandat			(₹)		IGST)	(₹)	
		ory)					(₹)		
							(C)		
				(A)	(B)	%	AMT	(D=B+C)	(E=DXA)
	SUPPLY OF SINGLE PHASE								
	NATURAL ORGANIC ESTER								
1	OIL FILLED COMPLETELY		Nos	350			b		
_	SELF PROTECTED (CSP)		1105	330					
	TRANSFORMER OF RATING								
	25KVA 6.35/0.240kV								
GRANI	GRAND TOTAL LANDED VALUE (₹)								
In words									
NOTE	NOTE O 1 C NO 1 C 1 C 1 C 1 C 1 C 1 C 1 C 1 C 1 C 1								

NOTE: Cost of all tests as per technical specification is to be included. No separate charges will be paid.

The Un-priced bid should be marked as "Quoted" and be submitted with Part – A

We declare that the following are our quoted prices in INR for the entire package.

Date:	Bidders Name:	
Place:	Bidders Address:	
Signature:	Designation:	.
Printed Name:	Common Seal:	

PRICE BID FORMAT	Page 2 of
NIT NO: CMC/BY/24-25/RS/SkS/SV/09	
[RFx Number: 2200000026]	
·	






Specification of Single Phase Oil Filled CSP Transformer

Specification no - BSES-TS-30-SPT-R0

Revision		0
Date		22/04/2022
Pages		36
Prepared by	Jeena Borana	Leins
	Vani Sood	Jan 3 7 1041 8 8
Reviewed by	Srinivas Gopu	toj
	Amit Tomar	Jist 2200 aproxi
Approved by	Gaurav Sharma	Causari
Approved by	Gopal Nariya	5///





TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

INDEX

Reco	rd of Revi	sion	3	
1.0	Scope o	f work	4	
2.0	Codes 8	k standards	4	
3.0	Major D	esign Criteria & Parameters of the Transformer	5	
4.0	Constru	ction & Design	7	
5.0	Fittings	and Accessories on Transformer	14	
6.0	Approve	ed make of components	16	
7.0	Quality a	assurance	16	
8.0	Progres	s Reporting	18	
9.0	Inspecti	on & testing	18	
10.0	Packing	, Shipping, Handling and Storage	22	
11.0	Deviatio	ns	23	
12.0	Drawing	& Data Submission matrix	24	
Anne	xure – A	Service Conditions	26	
Anne	xure – B	Technical Particulars of Natural Ester Oil	27	
Anne	xure – C	Guaranteed Technical Particulars (Data by Seller)	28	
Anne	Annexure – D Guaranteed Technical Particulars of Natural Ester oil			
Anne	xure – E	Recommended Spares (Data by Supplier)	36	



BSES-TS-30-SPT-R0

TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

Record of Revision

SI No.	Revision No	Item/Clause No.	Nature of change	Approved by

BSES-TS-30-SPT-R0



TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER


1. Scope of work

- 1.1 This specification covers design, engineering, manufacture, assembly, testing at manufacture's works, packing, transportation and delivery to site, supervision of erection, testing at site & commissioning and submission of complete documentation of CSP transformers to be used in HVDS system.
- 1.2 The transformer shall be complete with all components and accessories, which are necessary or usual for their efficient performance and trouble free operation under the various operating and atmospheric conditions specified in annexure A.
- 1.3 Such of the parts that may have not been specifically included, but otherwise form part of the transformer as per standard trade and/or professional practice and/or are necessary for proper operation of transformer, will be deemed to be also included in this specification.

2. Codes & standards

- 2.1 Materials, equipment and methods used in the manufacture of Transformer shall conform to the latest edition of below mentioned standards.
- 2.2 Vendor shall possess valid BIS Certification.

IS 1180 part 1	Outdoor type oil immersed distribution transformer upto and	
	including 2.5MVA,33kV	
IS 1180 part 3	Outdoor type oil immersed distribution transformer upto and including 2.5MVA, 33kV.	
	Part 3 Natural/Synthetic Organic Ester oil Liquid Immersed.	
IS 2026	Power Transformers	
IS 2026-4	Terminal Marking, tappings and Connections for Power	
	Transformers.	
IS:3347	Dimensions for Porcelain Transformer bushing	
IS 16659	Fluids for Electro technical Application- Unused Natural Esters	
	for Transformers and Similar Electrical Equipment	
IS-12444	Specification for Cu Wire rods	
IS-5484	Specification for Al Wire rods	
IS:10028	Code of practice for selection, installation & maintenance of	
	transformers	
IS 5561	Electrical Power Connectors	
IS 5	Colors for ready mix paints	
IS/IEC 60071	Co-ordination of Insulation.	
IEC 62770	Unused natural esters for transformers and similar electrical	





TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

	equipment	
IS2026-7/IEC 60076-7	Loading Guide for Oil-Immersed Power Transformers.	
IS 2026-8 /IEC 60076-8	Application Guide for Power Transformers.	
IS 2026-10/IEC 60076-10	Determination of Transformer Sound Levels.	
IS/IEC 60529	Degrees of Protection Provided by Enclosures (IP Code).	
IS/IEC 60947	Low-Voltage Switchgear and Control gear.	
IS/IEC 60137	Bushing for alternating voltage above 1000V	
IS:1271/IEC 60085	Thermal evaluation and classification of electrical insulation	
IEC 60076	Power transformers.	
IEC 60156	Method for Determination of the Electric Strength for Insulating	
	Oils.	
IEC 60445	Basic& Safety principles for man-machine interface, marking and identification, Identification of Equipment Terminals and conductor terminals	
IEEE C57.155	IEEE Guide for interpretation of Gases Generated in Natural	
	Ester and Synthetic Ester-Immersed Transformer	
DIN 42531 to 33	Specification for Outdoor Bushings	
ASTM B-49	Specification for Cu Wire rods	
ASTM B-233	Specification for Al Wire rods	
	Indian Electricity Rules	
	Indian Electricity Act	
	CBIP manual	

In the event of direct conflict between various order documents, the precedence of authority of documents shall be as follows –

- i. Guaranteed Technical Particulars (GTP)
- ii. This Specification
- iii Indian Standards / IEC standards
- iv Approved Vendor Drawings
- v Other documents

3. Major Design Criteria & Parameters of the Transformer


Sr No	Description	Data by purchaser
3.1	Voltage variation on supply side	+ / - 10 %
3.2	Frequency variation on supply side	+/ - 5 %



BSES-TS-30-SPT-R0

TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

3.3	Transient condition	- 20 % or + 10 % combined variation of
		voltage and frequency
3.4	Service Condition	Refer Annexure A
3.5	Location of equipment	Outdoor application
3.6	Reference design ambient	50 deg C
	temperature	
3.7	Type of transformer	Sealed type, completely self protected (CSP)
3.8	Type of construction	Core type, oil immersed
3.9	Type of cooling	Oil natural air natural (KNAN)
3.10	No of phases	Single phase on primary & secondary side
3.11	No of windings	Two (one each for primary & secondary)
3.12	Rated frequency (Hz)	50 Hz
3.13	Highest system voltage HV side	12kV
3.14	Lightning Impulse withstand voltage, kV peak	
3.14.1	For nominal system voltage of 11 kV	75
3.15	Power Frequency Withstand Voltage kV rms	
3.15.1	For nominal system voltage of HV	28
3.15.2	For nominal system voltage of LV	3
3.16	Thermal and Dynamic short circuit withstand	For 3 secs.
3.17	Method of 11kv system earthing	Effectively earthed at 11kv source
3.18	Rated voltage HV Phase to Neutral	11/√3 KV
3.19	Rated voltage LV	240V
3.20	Rated HV current	
3.20.1	16kVA	2.52A
3.20.2	25kVA	3.96A
3.20.3	50kVA	7.87A
3.21	Rated LV current	
3.21.1	16kVA	66A
3.21.2	25kVA	104A
3.21.3	50kVA	208A
3.22	Percentage Impedance at 75 deg C	4% with IS tolerance
3.23	Max Total losses(No Load+ Load Losses at 75°C) at 50% of the rated load, Watts	





3.23.1	16 kVA	82
3.23.2	25 kVA	110
3.23.3	50 kVA	210
3.24	Max Total losses (No Load+ Load Losses at 75°C) at 100% of the rated load , Watts	
3.24.1	16 kVA	224
3.24.2	25 kVA	300
3.24.3	50 kVA	590
3.25	Temperature rise over reference ambient of 50°C	
3.25.1	Top oil by thermometer 0 C	40° C
3.25.2	Winding by resistance 0 C	45° C
3.26	Reference standard	IS 1180 part 3/IS 1180 part 1
3.27	Overload Capability	As per IS 2026-part 7
3.28	Noise Level	As per IEC 60076-10
3.29	Minimum terminal clearance	
3.29.1	HV phase to earth	140 mm
3.29.2	LV phase to earth	40 mm

4. Construction & Design

4.1	Type	Double Copper wound, single phase, oil
		immersed with KNAN cooling with
		completely self protected (CSP)
4.2	Major Parts	
4.2.1	Tank	
4.2.1.1	Туре	Sealed type with bolted cover which
		seals the interior of the tank from
		atmosphere.
4.2.1.2	Material of Construction	Tank should be round and made of
		good quality sheet steel
4.2.1.3	Tank Thickness	Adequate for meeting the requirements
		of pressure and vacuum type tests as
		per IS 1180 (Part – 3/Part-1) It shall be
		stiffed to provide sturdy and robust
		construction to withstand extreme
		pressure conditions.



the tank shall be folded upward for at least 25 mm, to have sufficient overlap with vertical sidewall of the transformer. ii) All seams and joints shall be double welded iii) The tank should be capable of withstanding pressure and vacuum as per values specified in IS: 1180 (Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.	4.2.1.4	Tank features	i)	The circular base plate edges of
at least 25 mm, to have sufficient overlap with vertical sidewall of the transformer. ii) All seams and joints shall be double welded iii) The tank should be capable of withstanding pressure and vacuum as per values specified in IS: 1180 (Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.	7.2.1.7	Tank loatalos	'/	
overlap with vertical sidewall of the transformer. ii) All seams and joints shall be double welded iii) The tank should be capable of withstanding pressure and vacuum as per values specified in IS: 1180 (Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				•
transformer. ii) All seams and joints shall be double welded iii) The tank should be capable of withstanding pressure and vacuum as per values specified in IS: 1180 (Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				•
ii) All seams and joints shall be double welded iii) The tank should be capable of withstanding pressure and vacuum as per values specified in IS: 1180 (Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				•
double welded iii) The tank should be capable of withstanding pressure and vacuum as per values specified in IS: 1180 (Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.			::\	
iii) The tank should be capable of withstanding pressure and vacuum as per values specified in IS: 1180 (Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank shall be such that even under extreme or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.			11)	-
withstanding pressure and vacuum as per values specified in IS: 1180 (Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				
as per values specified in IS: 1180 (Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.)	
(Part – 3/Part-1) iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				- .
iv) The tank cover shall have plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				•
plasticized surface at the top to guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.			l	,
guard against birdage faults. Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.			iv)	
Alternatively, suitable insulating shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				•
shrouds shall be provided on the bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				
bushing terminals. v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				
v) The transformer shall have a self pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				•
pressure venting system. vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				•
vi) Steel surface of the tank shall be prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.			v)	
prepared by sand blast or chemical cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				,
cleaning including phosphating as per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.			vi)	
per IS: 3618. vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				prepared by sand blast or chemical
vii) The space on the top of oil shall be filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				
filled with dry air or nitrogen. The nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				•
nitrogen plus oil volume inside the tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.			vii)	•
tank shall be such that even under extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				
extreme operating conditions, the pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				
pressure generated inside the tank does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				
does not exceed 0.4 Kg/cm2 positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				
positive or negative. viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				. •
viii) Heat resistance paint (Hot oil proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				does not exceed 0.4 Kg/cm2
proof) shall be provided inside the tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				positive or negative.
tank. On external surface one coat of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.			viii)	• •
of Thermo setting powder paint or two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				proof) shall be provided inside the
two coats of zinc chromate followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				tank. On external surface one coat
followed by two coats of synthetic enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				<u> </u>
enamel paint of shade conforming to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				two coats of zinc chromate
to No.631 of IS:-5 shall be provided. The overall thickness of the paint shall be minimum150 micron.				followed by two coats of synthetic
provided. The overall thickness of the paint shall be minimum150 micron.				enamel paint of shade conforming
the paint shall be minimum150 micron.				to No.631 of IS:-5 shall be
micron.				provided. The overall thickness of
				the paint shall be minimum150
422 Core				micron.
T.Z.Z	4.2.2	Core		




4.2.2.1	Material	High grade , non ageing, low loss, high permeability, grain oriented, cold rolled silicon steel lamination
4.2.2.2	Grade	Premium Grade minimum M3 or better
4.2.2.3	Lamination thickness	0.23 mm Max.
4.2.2.5	Maximum Flux Density at 12.5 % over excitation / over fluxing	1.9 T
4.2.26	No load current	2% and 4% of RFLC at 100% and 112.5% Max
4.2.3	Winding	
4.2.3.1	Material	Electrolytic Copper
4.2.3.2	Winding connection	
4.2.3.2.1	HV Winding	Both ends of the primary winding shall be brought out through an appropriate HV bushings, one end of HV winding shall be externally earthed.
4.2.3.2.2	LV Winding	The secondary winding shall be connected to two LV bushing
4.2.3.3	Maximum Current Density allowed	3 Amp per sq mm
4.2.3.4	Winding Insulation	DPC insulation shall be used for HV and LV winding wires and electrical grade plain insulation Kraft paper for interleaving, no material, which can be affected by the action of oil under the operating conditions of the transformers, shall be used in the transformers or leads of the bushings.
4.2.3.5	Design features	 i) The core and coil assembly shall be securely held in position to avoid any movement under short-circuit conditions. ii) All turns of windings shall be adequately supported to prevent movement, in cases where turns are spaced out, a suitable inter-turn packing shall be provided. iii) The type of winding provided for HV side shall be preferably disc type or spiral winding. iv) The type of winding for LV side shall be preferably cylindrical, layer
4.2.4	Transformer Oil	
4.2.4.1	Туре	i) Natural Organic Ester oil should be



		in accordance with specification as per Annex B of this document. ii) One sample of oil drawn from every lot of transformer offered for inspection should be tested at CPRI/ERDA for tests as listed in IS16659. The cost of this testing should be included within the cost of transformer.
4.2.5	Bushings and Terminations	
4.2.5.1	Type of HV side bushing	Outdoor, Porcelain clad, creepage as per 31mm/kV(min)with voltage class of 12kV
4.2.5.1.1	Essential provision for HV side line bushing	HV bushings shall be fitted with molded heat shrinkage insulating covers / shrouds suitable for Aerial Bunched Conductor to provide protection of the bushing palm.
4.2.5.2	Type of LV side bushing	Outdoor, Porcelain clad, creepage as per 31mm/kV(min) with voltage class of 1.1kV.
4.2.5.3	Arcing Horns	Not required
4.2.5.4	Termination on HV side bushing	i) The bushing palm is suitable for termination of 1CX 150 sqmm Aerial bunched cables, with bolted type clamping arrangement both in horizontal and vertical directions. ii) In case of copper/copper alloy stems, suitable bimetallic clamps with bolted type arrangement described above shall be used.
4.2.5.5	Termination of LV side bushing	Suitable for termination of 2 runs of 1CX95 sq mm XLPE cable.
4.2.5.6	Continuous Current rating	Minimum 20 % higher than the rated
4.2.5.0		current of the transformer



4.2.6	LT cable box	 i) The LT cable box shall be provided as an integral part of the transformer designed for outdoor duty with minimum IP-55 protection. ii) MCCB is to be provided after LT bushing in the LT cable box iii) The cable box shall be equipped with LED to indicate ON/OFF& tripping of LT MCCB. On resetting of LTMCCB the tripping LED shall be automatically switched off. iv) LT bushing shall be inside the distribution box and a facility for sufficient outgoing feeders through cable glands shall be provided.
4.2.7	Lightning Arrestor	,
4.2.7.1	Туре	Non linear resistance type
4.2.7.2	Rated Voltage of Arrestor, kV rms	9
4.2.7.3	Nominal Discharge Current, kA peak	5
4.2.7.4	Mounting arrangement	i) Lightning arrestor shall be mounted external to the transformer and shall be suitable for outdoor type duty. ii) The line terminal of the surge arrestor shall be connected the HV bushing and the earth terminal of the surge arrestor shall be solidly connected to a separate earth externally.
4.2.8	Transformer Mounting Arrangement	The transformers are to be mounted on single pole MS – I channel or tubular pole or PCC pole, the transformer therefore shall be provided with suitable and robust mounting arrangement. The mounting arrangement drawing shall be furnished for approval.
4.2.9	Hardware	
4.2.9.1	External	Stainless Steel
4.2.9.2	Internal	Cadmium plated except special hardware for frame parts and core assembly as per manufacturer's design
4.2.10	Gasket	Gaskets shall be made of synthetic rubber or synthetic rubberized cork resistant to hot transformer ester





		liquid. ii) Gasket shall confirm to Type III as per IS 11149/Type C as per IS 4253 (Part 2) and shall be compatible with high contact temperature i.e thermal class of 130°C.
4.2.11	Painting of transformer	
4.2.11.1	Surface preparation	By 7 tank pretreatment process or shot blasting method
4.2.11.2	Finish on internal surfaces of the transformer	Heat resistant and oil resistant paint two coats. Paint shall neither react nor dissolve in hot transformer insulating oil.
4.2.11.3	Finish on outer surface of the transformer	Battle ship grey shade 632 IS 5 Polyurethane paint two coats, overall paint thickness shall be 150 microns (min)
4.3	Transformer Protection	
4.3.1	HV Protection	 i) HV protection shall be provided by an internally mounted HV fuse in series with the primary winding. ii) The option of using 11 KV fuse tube (preferably made of fiber glass), connected externally between the terminals of the lightning arrestor and the HV bushing can also be explored. The arrangement shall be such that the fuse tube remains in position when the fuse element inside the fuse tube blows off.
4.3.2	LT Protection	
4.3.2.1	MCCB Type	The MCCBs shall be trip free type with quick make and break design. The design of the operating mechanism of the circuit breaker shall be such that it shall have only two positions i.e. 'ON' and 'OFF', it shall not require resetting before being switched to 'ON' position.
4.3.2.2	Utilization Category	Α
4.3.2.3	Interrupting medium	Air
4.3.2.4	Design	Molded case
4.3.2.5	Type of operation	Independent manual closing
4.3.2.6	Suitability for isolation	Not suitable for isolation
4.3.2.7	Provision for maintenance	Maintainable



Number of poles Rated uninterrupted current	2			
Rated uninterrupted current				1
(enclosed)	100	100 A 160 A 31		315 A
Voltage rating	250/4	115		•
Rated insulation voltage	1kV			
Rated impulse withstand voltage	8kV			
Ultimate Breaking Capacity Icu	35 K	A min.		
Service Breaking capacity Ics	35 K	A min.		
Rated frequency	50Hz	•		
Rated duty	Unint	errupted	duty	
Trip current characteristics:		· · ·		
Type of release	Therr	mal-Magı	netic	
Overload setting				of In.
	Inste	p of 10%		
Short circuit settings	250%	% to 900°	% of In. Instep	s of 50%
Trip time at rated uninterrupted current	>2.5	>2.5 hrs		
Trip time at 2.5 Setting times normal current	< 1 m	ninute		
Trip time at 6 times normal current setting	< 5 secs.			
Trip time at 9 times normal current setting	40 millisec.			
MCCB	ii) T the property of the prop	current of LT MC rarious of lawn of ondicate of the LT MC rapacity of the HT function with LT MC rate of the HT function of the	urves. The checces and 11 current multiple in the same coordination is and the HT for CCB shall open of transformer use shall act as a for LT system of the close of CCB compared to the close of the cl	naracteristics KV fuse for les shall be e sheet to between the use. erate with above rated unit. elected such a back up m faults and co-ordination elected such e for in rush
	Rated insulation voltage Rated impulse withstand voltage Ultimate Breaking Capacity Icu Service Breaking capacity Ics Rated frequency Rated duty Trip current characteristics: Type of release Overload setting Short circuit settings Trip time at rated uninterrupted current Trip time at 2.5 Setting times normal current Trip time at 6 times normal current setting Trip time at 9 times normal current setting Coordination of HT Fuse and LT	Rated impulse withstand voltage Rated impulse withstand voltage Ultimate Breaking Capacity Icu Service Breaking capacity Ics Rated frequency Rated duty Unint Trip current characteristics: Type of release Overload setting Varia Inste Short circuit settings Trip time at rated uninterrupted current Trip time at 2.5 Setting times normal current Trip time at 6 times normal current setting Coordination of HT Fuse and LT MCCB INV INV INV INV INV IV) T It IV IV) T It IV IV) T IT	Rated insulation voltage Rated impulse withstand voltage Ultimate Breaking Capacity Icu Service Breaking capacity Ics Rated frequency Rated duty Trip current characteristics: Type of release Overload setting Variable type Instep of 10% Short circuit settings Trip time at rated uninterrupted current Trip time at 2.5 Setting times normal current Trip time at 9 times normal current setting Coordination of HT Fuse and LT MCCB Rated impulse withstand voltage WkV 35 KA min. 35 KA min. 36 KA min. 37 KA min. 38 KA min. 39 KA mi	Rated insulation voltage Rated impulse withstand voltage Ultimate Breaking Capacity Icu Service Breaking capacity Ics Rated frequency Fated duty Trip current characteristics: Type of release Overload setting Trip time at rated uninterrupted current Trip time at 2.5 Setting times normal current Trip time at 9 times normal current setting Coordination of HT Fuse and LT MCCB Tik MCCB and 11 Tik MCCB and 11 Tik MCCB and 11 Tik MCCB and the HT fit



TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

v) The HT fuse shall be selected such that it shall operate instantaneously for all internal faults in the transformer.
vi) The supplier shall carry out coordination test, as indicated above, on minimum one transformer out of every 50 transformers and this shall form an Acceptance Test by the purchaser. Co-ordination of LT MCCB for external faults and HT fuse for internal faults complete with expected fault currents and I²t value of MCCB /HT fuse shall be assured/proved.

5.

6. Fittings and Accessories on Transformer

5.1	Rating and Diagram Plate	Required
5.1.1	Material	Anodized aluminum 16SWG
5.1.2	Background	SATIN SILVER
5.1.3	Letters, diagram & border	Black
5.1.4	Process	Etching
5.1.5	Rating and Diagram Plate details	Following details shall be provided on rating and diagram plate as a minimum i) Type/kind of transformer with winding material ii) standard to which it is manufactured iii) manufacturer's name; iv) transformer serial number; v) month and year of manufacture vi) rated frequency in Hz vii) rated voltages in kV viii) number of phases ix) rated power in kVA x) type of cooling (KNAN) xi) rated currents in A xii) 1.2/50µs wave impulse voltage withstand level in kV xiii) power frequency withstand voltage in kV xiv) impedance voltage at rated current



		and frequency in percentage xv) Max. Total losses at 50 % rated load xvi) Max. Total losses at 100 % rated load xvii) Load loss at 50% & 100% rated load xviii) Energy efficiency level. xix) continuous ambient temperature at which ratings apply in deg C xx) top oil and winding temperature rise at rated load in deg C; xxi) winding connection diagram with voltage, current and power xxii) transport weight of transformer xxiii) weight of core and windings xxiv) Weight of core xxv) Weight of winding xxvi) total weight xxvii) volume of oil xxviii) weight of oil xxix) name of the purchaser xxx) PO no and date xxxi) Guarantee period xxxii) Manufacturer call center number &
5.2	Two earthing terminals with the earthing symbol	email id Required
5.3	Lifting lugs for complete transformers as well as for core & winding	Required
5.4	Bird guard.	Required
5.5	Pressure relief valve.	Required
5.6	Non return valve.	Required
5.7	Terminal connector	Required
5.8	HV side neutral earthing strip.	Required
5.9	Lightning arrestor	Required
5.10	Terminal marking plate	Required
5.11	Fittings as per IS 1180	Required
5.12	Additional fittings for CSP type of distribution transformers, if any. The fittings and accessories listed are	



TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

indicative only and any other fittings	
and accessories which are generally	
required for satisfactory operation of	
the transformer are to be provided	
without any extra cost	

7. Approved make of components

6.1	Bushings	Baroda Bushing/CJI/Jaipur glass
6.2	CRGO	Nippon/JFE/Posco/Thyssen Krupp
6.3	Copper	Birla copper/Sterlite
6.4	Pre compressed Pressboard	Raman Board, Mysore/ Senapathy Whiteley, Dupont
6.5	Laminated Wood	Permalli Wallance / Rochling Engineers
6.6	Natural Ester Oil	Midel/Cargil
6.7	Mineral Oil	Apar/Savita/Raj Petro
6.8	Steel	TATA/Jindal/SAIL
6.9	Surge arrestor	Electrolite Power/Oblum/Tyco
6.10	MCCB	ABB/L&T/Schneider
6.11	Fuse	ERMCO,USA

Note – Any other make of component to be approved by purchaser

8. Quality assurance

T = 4	10 B A	T	1 10 11 6
7.1	Quality Assurance program	lop	pe submitted before contract award.
		Prog	gram shall contain following
		i)	The structure of the organization
		ii)	The duties and responsibilities
			assigned to staff ensuring quality of
			work.
		iii)	The bidder should have qualified
			technical & dedicated QA
			personnel at various stages of
			manufacture & testing.
		iv)	Factory inspection of bidder may
			be carried out to ascertain the
			quality system and process in
			place at manufacturing facility.
			The same is applicable to bidders
			not approved with BSES.
		v)	The system for purchasing, taking
			delivery and verification of materials



		vi) The system for ensuring quality of workmanship
		vii) The system for control of documentation
		viii) The system for the retention of records
		ix) The arrangements for the Supplier's internal auditing
		x) A list of the administration and work procedures required to achieve and verify Contract's quality requirements. These procedures shall be made readily available to the Purchaser for inspection on request
7.2	Quality Plan	To be submitted by the successful
1.2	Quality Flam	bidder for approval. Plan shall contain
		following as a minimum
		i) An outline of the proposed work
		and programme sequence
		ii) The structure of the Supplier's
		organization for the contract
		iii) The duties and responsibilities
		assigned to staff ensuring quality of work for the contract
		iv) Inspection Hold and notification
		points mutually agreed.
		v) Submission of engineering
		documents required by the specification
		vi) The inspection of materials and
		components on receipt
		vii) Reference to the Supplier's work
		procedures appropriate to each
		activity
		viii) Inspection during
		fabrication/construction
		ix) Final inspection and test
		x) Successful bidder shall include
		submittal of Mills invoice, Bill of
		lading, Mill's test certificate for
		grade, physical tests, dimension,
		specific watt loss per kG for the



TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

	core material to the purchaser for
	verification in the quality plan
	suitably

9.

10. Progress Reporting

8.1	Outline Document	To be submitted for purchaser approval
		for outline of production, inspection,
		testing, packing, dispatch,
		documentation programme
8.2	Detailed Progress report	To be submitted to Purchaser once a
		month containing
		i) Progress on material procurement
		ii) Progress on fabrication
		iii) Progress on assembly
		iv) Progress on internal stage
		inspection
		v) Reason for any delay in total
		programme
		vi) Details of test failures if any in
		manufacturing stages
		vii) Progress on final box up
		viii) Constraints
		ix) Forward path

11.

12. Inspection & testing

9.1	Inspection and Testing during manufacture	Only type tested equipment shall be acceptable
9.1.1	Tank	 i) Check for physical properties of materials for lifting lugs, jacking pads etc. All load bearing welds, including lifting lug welds shall be subjected to required load tests. ii) Certification of all test results. iii) Oil leakage test iv) Vacuum and Pressure test on tank as type test as per IS 1180
9.1.2	Core	 i) Sample testing of core material for checking specific loss, bend properties, magnetization characteristics and thickness. ii) Check on the quality of varnish if used on the stampings.




			a) Measurement of thickness and
			hardness of varnish on
			stampings.
			b) Solvent resistance test to check
			that varnish does not react in
			hot oil.
			c) Check over all quality of varnish
			by sampling to ensure uniform
			hipping colour, no bare spots.
			No ever burnt varnish layer and no bubbles on varnished
			surface.
		:::\	
		iii)	Check on the amount of burns.
			Bow check on stampings.
		v)	Check for the overlapping of
			stampings. Corners of the sheet
		:\	are to be apart.
		VI)	Visual and dimensional check
		::\	during assembly stage.
		VII)	Check on complete core for
			measurements of iron-loss and
			check for any hot spot by exciting
			the core so as to induce the
			designed value of flux density in the
			core.
		VIII)	Check for inter laminar insulation
			between core sectors before and
			after pressing.
		IX)	Visual and dimensional checks for
			straightness and roundness of
			core, thickness of limbs and
			suitability of clamps.
		X)	High voltage test (2 KV for one
		.,	minute) between core and clamps.
0.4.0		xi)	Certification of all test results.
9.1.3	Insulating Materials	i)	Sample check for physical
		::\	properties of materials.
		ii)	Check for dielectric strength. Visual and dimensional checks.
		iii)	Check for the reaction of hot oil on
		iv)	-
		W	insulating materials. Certification of all test results.
0.1.4	Mindings	v)	
9.1.4	Windings	i)	Sample check on winding



	T	I	and uster for machanical
			conductor for mechanical
			properties and electrical
			conductivity.
		ii)	Visual and dimensional check on
			conductor for scratches, dept.
			mark etc.
		iii)	Sample check on insulating paper
			for PE value, Bursting strength,
			Electric strength.
		iv)	Check for the reaction of hot oil on
			insulating paper.
		v)	Check for the bending of the
			insulating paper on conductor.
		vi)	Check and ensure that physical
			condition of all materials taken for
			winding is satisfactory and free of
			dust.
		vii)	Check for absence of short circuit
			between parallel strands.
		viii)	Check for Brazed joints wherever
			applicable.
		ix)	Measurement of voltage ratio to
			be carried out when core/ yoke is
			completely restocked and all
			connections are ready.
		x)	Certification of all test results.
9.1.4.1	Checks before drying process	i)	Check conditions of insulation on
	, , ,	'	the conductor and between the
			windings.
		ii)	Check insulation distance
		,	between high voltage connection
			distance between high voltage
			connection cables and earthed
			and other live parts.
		iii)	Check insulation distance
		'	between low voltage connection
			and earthed and other parts.
		iv)	Insulation test of core earthing.
		v)	Check for proper cleanliness
		vi)	Check tightness of coils i.e. no
		,	free movement.
		vii)	Certification of all test results.
9.1.4.2	Checks during drying process	i)	Measurement and recording of
J. 1. 7 .2	Chooks during drying process	'/	Moadaromont and recording of



		tomporative and desire times
		temperature and drying time
		during vacuum treatment.
		ii) Check for completeness of drying.
0.4.5	0.1	iii) Certification of all test results.
9.1.5	Oil	As per IS 16659/ IEC 62770
9.1.6	Test on fittings and accessories	As per manufacturer's standard
9.2	Routine tests	The sequence of routine testing shall
		be as follows
		i) Visual and dimension check
		ii) Measurements of voltage ratio
		iii) Measurements of winding
		resistance
		iv) Measurements of insulation
		resistance and polarization index
		v) Separate sources voltage
		withstand test.
		vi) Measurement of iron losses and
		exciting current at rated frequency
		and 90%, 100% and 112.5% rated
		voltage.
		vii) Induced voltage withstand test.
		viii) Load losses measurement at 50 %
		& 100 % of load.
		ix) Impedance measurement
		x) Routine test of tanks
		xi) HT fuse and LT MCCB
		coordination test
		xii) Oil leakage test on transformer
		xiii) Certification of all test results.
		xiv) Temperature Rise Test #
		#Tamporature rise test may be
		#Temperature rise test may be
		necessary to be carried one unit/lot.
		Purchaser's engineer, will at its
		discretion, select transformer for temp.
		rise test from any lot offered for
		inspection at manufacturer's works
		and witness the same for
		comparison with ERDA/CPRI type
	 	test results
9.3	Type Tests	On one transformer of each rating and
		type at CPRI/ERDA.
		i) Impulse withstand test





		ii) Temperature rise test as per IS iii) Dynamic & Thermal (3 sec) Short circuit test iv) Air pressure test v) Pressure and Vacuum test on tank vi) Dissolved gas analysis before and after Temperature Rise Test vii) Oil testing to be tested at CPRI/ERDA labs, whose samples shall be selected & sealed by customer.
		Note – Purchaser may choose to carry out short circuit, impulse & temperature rise test on one unit from a lot offered from inspection at CPRI/ERDA
9.3.2	Notification to bidders	In case bidder had conducted type & special tests from CPRI/ERDA on BSES design and there is no design change in the transformer less than 10 years from the date of the bid opening, then bidder need not to conduct the type test from CPRI/ERDA. The bidder shall submit the under taking that there is no change in design with respect to type tested design.
		The product offered must be of type tested quality. In case the product offered is never type tested the same as per above list to be conducted by bidder at his own cost at CPRI/ERDA. The test report shall not be more 5 years old
9.4	Customer Hold Point	i) GTP & Drawings approval ii) Tank Pressure & vacuum Test iii) Core & Coil Stage inspection of each lot to be offered

13. Packing , Shipping, Handling and Storage

10.1	Packing	
10.1.1	Packing protection	Against corrosion, dampness, heavy rains, breakage and vibration
10.1.2	Packing for accessories and spares	Robust wooden non returnable packing



TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

		case with all the above protection
10.1.3	Packing details	On each packing case details required
		as follows
		i) Individual serial number;
		ii) Purchaser's name;
		iii) PO number;
		iv) Destination;
		v) Supplier's name;
		vi) Name and address of supplier's agent
		vii) Description and quantity
		viii) Manufacturer's name
		ix) Country of origin
		x) Case measurements
		xi) Gross and net weights in
		kilograms
		xii) All necessary slinging and
		stacking instructions.
10.2	Shipping	The bidder shall ascertain at an early
		date and definitely before the
		commencement of manufacture, any
		transport limitations such as weights,
		dimensions, road culverts, overhead
		lines, free access etc. from the
		manufacturing plant to the project site;
		and furnish to the Purchaser
		confirmation that the proposed packages
		can be safely transported, as normal or
		oversize packages, upto the plant site.
		Any modifications required in the
		infrastructure and cost thereof in this
		connection shall be brought to the notice
40.0	100	of the Purchaser
10.3	Handling and Storage	As per manufacturer's instruction

14.

15. Deviations

		Deviations from this Specification shall be provided in excel			
		sheet with tender by reference to the Specification			
11.1	Deviation	clause/GTP/Drawing and a description of the alternative			
		offer. In absence of such a statement, it will be assum			
		that the bidder complies fully with this specification.			



16. Drawing & Data Submission matrix

Document submission shall be as per the matrix given below. All documents/drawing shall be provided in soft copy (in pen drive) for each section. Language of the documents shall be English only. Deficient/improper drawing submission may liable for rejection.

S No.	Documents to be submitted	Bid	Approval	Pre Dispatch
12.1	Copy of specification along with company seal & signature on each page.	Required	Required	·
12.2	Guaranteed technical particulars	Required	Required	
12.3	Outline dimension drawing for each major component, general arrangement drawing showing component layout an general schematic diagrams.	Required	Required	
12.4	Type test certificates, where available, and sample routine test reports	Required	Required	
12.5	Detailed reference list of customers already using equipment offered during the last 5 years with particular emphasis on units of similar design and rating	Required		
12.6	Performance certificates executed in last 5 years	Required		
12.7	Details of manufacturers quality assurance standard and programme and ISO 9000 series or equivalent national certification.	Required		
12.8	Deviations from this specification. Only deviations approved in writing before award of contract shall be accepted.	Required		
12.9	Recommended spare parts and consumable items for the five years of operation with prices and spare parts catalogue with price list for future requirements.	Required		
12.10	Transport / shipping dimension and weights, space required for handling parts for maintenance	Required		
12.11	Write up on oil preservation system.	Required	Required	
12.12	Quality assurance program.	Required	Required	
12.13	Programme for production and testing		Required	



	1 1	
12.14 General description of the	Required	
equipment and all components,		
including brochures		
12.15 Detailed dimension drawing for all	Required	
components ,general arrangement		
drawing showing detailed		
component layout and detailed		
schematic and wiring drawings for		
all components like Lightning		
arrestor, birdguard, bushings		
12.16 Calculations to substantiate choice	Required	
of electrical, structural, mechanical		
component size, ratings		
12.17 Termination arrangement	Required	
12.18 Flow diagram of cooling system	Required	
showing no. of cooling banks		
12.19 Drawings of major components like	Required	
bushing,LA, MCB etc		
12.20 Lists of makes of all fittings and	Required	
accessories		
12.21 Statement drawing attention to all	Required	
exposed points in the equipment at		
which contact with or in close		
proximity to other metals and stating		
clearly what protection is employed		
to prevent corrosion at each point		
12.22 Detailed installation and	Required	
commissioning instructions		
12.23 Inspection and test reports carried		Required
out in manufacturers works		•
12.24 Test certificates of all bought out		Required
items.		·
12.25 Operation and maintenance		Required
instructions as well as trouble		-
shooting charts.		



TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

17. Annexure – A Service Conditions

1.0	Delhi Atmospheric conditions	
1.1	Average grade atmosphere :	Heavily polluted, dry
1.2	Maximum altitude above sea level	1000 M
1.3	Ambient Air temperature	Highest 50 deg C, Average 40 deg C
	Design ambient temperature	50 deg C
1.4	Relative Humidity	90 % Max
1.5	Seismic Zone	4
1.6	Rainfall	750 mm concentrated in four months






18. Annexure – B Technical Particulars of Natural Ester Oil

The Natural Ester Oil shall be certified as K Class as per IS 16659/IEC 62770.


Sr. No	Item description	Specification requirement
4.1.0	Physical property	
4.1.1	Appearance	Clear, free from sediments and suspended matter.
4.1.2	Viscosity	
4.1.2.1	At 100° C, Max	15 mm2/sec
4.1.2.2	At 40°, , Max	50 mm2/sec
4.1.3	Pour point , Max	-10° C
4.1.4	Water content, Max	200 mg/kg (ppm)
4.1.5	Density at 200C, Max	1.0 g/ cm ³
4.2.0	Electrical property	
4.2.1	Dielectric breakdown	65kV
	voltage (2.5 mm gap), Min	
4.2.2	Dielectric Dissipation factor	0.05
	(Tanδ) at 900 C, Max	
4.3.0	Chemical property	
4.3.1	Soluble acidity, Max	0.06 mg KOH/gm
4.3.2	Corrosive sulfur	Non corrosive
4.3.3	Total additives, Max	weight fraction 5%
4.4.0	Performance-After oxidation	
	stability test	
4.4.1	Total acidity, Max	0.6 mg KOH/g
4.4.2	Viscosity at 40 ⁰ C, Max	30% increase over the initial value
4.4.3	Dielectric Dissipation factor	0.5
	(Tanδ) at 90 ⁰ C, Max	
4.5.0	Health, safety and	
	environment (HSE)	
4.5.1	Fire point, Min	300° C
4.5.2	Flash point, Min	250°C
4.5.3	Biodegradation	Readily biodegradable






19. Annexure – C Guaranteed Technical Particulars (Data by Seller)

S. No.	Description	Specified/Required	Offered
1.0	Name of manufacturer		
2.0	Туре		
3.0	Ratings		
3.1	Nominal Continuous Rating, KVA	16/25/50kVA	
3.2	Rated voltage-HV, Volts	11/√3 kV	
3.3	Rated voltage-LV, Volts	240V	
3.4	Rated current-HV, Amps		
3.5	Rated current-LV, Amps		
3.6	No load voltage ratio		
3.7	Number of phases		
3.8	Frequency, Hz	50 Hz	
4.0	Connections		
4.1	High voltage		
4.2	Low voltage		
5.0	Method of cooling	KNAN	
6.0	Impedance voltage at rated voltage and frequency at 75°C	4% with IS tolerance	
6.1	Impedance		
6.2	Reactance		
6.3	Resistance		
7.0	Resistance of the winding at 75°C in ohm		
7.1	HV		
7.2	LV		
8.0	Guaranteed maximum Total Losses (no load losses+load losses at 75 deg.C), Watt		
8.1	50% of load		
8.2	100% of load	as per Spec Cl 3.24	
8.3	No Load Loss (Max)	as per Spec Cl 3.25	
8.4	Total I ² R losses of windings @ 75 deg C, Watt		
8.5	Total stray loses @ 75 deg C, Watt		
8.6	Total Load losses (Max.), Watt		
8.7	No load loss at maximum permissible voltage and frequency (approx.), Watt		
9.0	Temperature rise over reference ambient of 50° C		
9.1	Top oil by thermometer	35° C	
9.2	Winding by resistance	40° C	






9.3	Townsersture of bottoot and in the		i I
9.3	Temperature of hottest spot in the winding at full load, ⁰ C		
10.0	Efficiency		
10.1	Efficiency at 75°C and unity power		
10.1	factor, %		
10.1.1	at 110% load		
10.1.1	at 100% load		
10.1.2	at 80% load		
10.1.4	at 60% load		
10.1.4	at 40% load		
10.1.6	at 20% load		
10.1.0	Efficiency at 75°C and 0.8 power		
10.2	factor lag, %		
10.2.1	at 110% load		
10.2.1	at 100% load		
10.2.3	at 80% load		
10.2.3	at 60% load		
10.2.5	at 40% load		
10.2.6	at 20% load		
10.2.0	Maximum efficiency at 75°C, %		
10.3	Load and power factor at which it		
10.4	Occurs		
	Occurs		
11.0	Regulation, (%)		
11.1	Regulation at full load at 75° C		
11.1.1	at unity power factor		
11.1.2	at 0.8 power factor lagging		
11.2	Regulation at 112.5% load at		
	75 ⁰ C		
11.2.1	at unity power factor		
11.2.2	at 0.8 power factor lagging		
12.0	Details of tank		
12.1	Туре	Sealed type with	
		bolted cover which	
		seals the interior of	
		the tank from	
40.0	NA-t	atmosphere.	
12.2	Material	Tank should be round and made of	
		good quality sheet	
		steel	
12.3	Thickness of tank sheet	3,661	
12.3.1	Sides, mm		
12.3.1	Top, mm		
12.3.2	Bottom, mm		
12.3.3	Confirmation of Tank designed and		
12.7	tested for Vacuum, Pressure As per IS		
	1180(Yes/ No)		
<u> </u>		<u> </u>	Page 20 of






12.4.1	Vacuum mm of Hg. / (kN/m²)	As per IS 1180
12.4.2	Pressure mm of Hg.	7.0 [6.1.0]
12.5	Is the tank lid sloped?	Yes
13.0	Core	
13.1	Туре	Core
13.2	Core material grade	Premium grade minimum M3 or better
13.3	Core lamination thickness in mm	
13.4	Insulation of lamination	With insulation coating on both sides
13.5	Details of core	
13.5.1	Core material grade	Premium grade minimum M3 or better
13.5.2	Diameter, mm	
13.5.3	Cross sectional area, mm ²	
13.5.3.1	Gross, mm ²	
13.5.3.2	Net, mm ²	
13.5.4	Window height, mm	
13.5.5	Limb center, mm	
13.5.5	Weight of stamping in core and yoke separately	
13.5.6.1	Core, kgs	
13.5.6.2	Yoke, kgs	
13.5.6.3	Total, kgs	
13.6	Design flux density at rated voltage , Tesla	
13.7	Maximum flux density at 12.5 % over excitation /over fluxing, Tesla	1.9 Tesla Max allowed
13.8	Guaranteed No Load current at 100% rated voltage , Amps	
13.8.1	HV	
13.8.2	LV	
13.9	Guaranteed No Load current At 110% rated voltage, Amps	
13.9.1	HV	
13.9.2	LV	
14.0	HV coil construction details	
14.1	Type of winding	
14.2	Size of conductor (Bare), mm	
14.3	Cross sectional area of conductor, mm ²	
14.4	Number of coils per limb	
14.5	Outer diameter of coil, mm	
14.6	Inner diameter of coil, mm	






14.7	Insulation of conductor		
14.7	Interlayer reinforcement detail		
14.9	Current at full load, Amp		
14.10	Normal working current density,		
14.10	Amp/mm ²		
14.11	End turn insulation		
14.11	Weight of bare conductor used in one		
14.12	leg of HV, kg		
14.13	Weight of insulated conductor used in one leg of HV, kg		
14.14	Number of turns per leg		
14.15	Length of mean turns, mm		
14.16	Axial length, mm		
15.0	LV coil constructional details		
15.1	Type of winding		
15.2	Size of conductor (Bare), mm		
15.3	Cross sectional area of conductor, mm ²		
15.4	Number of coils per limb		
15.5	Outer diameter of coil, mm		
15.6	Inner diameter of coil, mm		
15.7	Insulation of conductor		
15.8	Interlayer reinforcement detail		
15.9	Current at full load, Amp		
15.10	Normal working current density,		
	Amp/mm ²		
15.11	End turn insulation		
15.12	Weight of bare conductor used in one leg of LV, kg		
15.13	Weight of insulated conductor used in one leg of LV, kg		
15.14	Number of turns per leg		
15.15	Length of mean turns, mm		
15.16	Axial length, mm		
16.0	Insulation details material and size		
16.1	HV coil end packing	TUP paper	
16.2	LV coil end packing		
16.3	Inter coil spacer of HT sections		
16.4	Bottom core strip insulation		
16.5	Yoke insulation		
16.6	Clamp insulation		
16.7	Inter phase barrier		
16.8	Core wrap		
16.9	Cylindrical insulation between HT & LT		
16.10	Type of blocks used between coils		
17.0	Details of clearances		





	<u> </u>	, , , , , , , , , , , , , , , , , , ,
17.1	Internal clearance between inner walls	
	of tank and core coil assembly unit,	
	mm	
17.2	Radial clearance between LV and HV	
	winding, mm	
17.3	Phase to phase clearance between	
	HV limb, mm	
17.4	Clearance from top of the yoke to the	
	inside of the top cover of tank, mm	
17.5	Radial clearance of LV coil from core,	
	mm	
17.6	Horizontal duct between HT sectional	
	coil	
17.7	End clearance of HT coil from yoke,	
	mm	
17.8	Minimum clearance between core and	
	tank bottom, mm	
18.0	Impulse test voltage of winding for	
	1.2/50 micro seconds wave according	
	to relevant IS	
18.1	HV	
18.2	LV	
19.0	Volts per coil of HV winding, Volts	
20.0	Approximate volts per layer of HV	
	winding, Volts	
21.0	Induced over voltage test at double	
	frequency	
22.0	Permissible duration of	
	overload following continuous	
	running at normal rated load in	
	ambient temperature of	
	50°C	
22.1	10%overload	
22.2	20%overload	
22.3	30%overload	
23.0	RMS value of symmetrical short circuit	
	current which the transformer can	
	withstand and its duration	
24.0	Terminal arrangement of HV side	
25.0	Terminal arrangement of LV side	
26.0	Particulars of HV bushing	
27.1	Make	
27.2	Туре	
27.3	Dry withstand voltage for one minute	
27.4	Wet withstand voltage for thirty	
	minutes	
27.5	Voltage rating	
27.6	Impulse withstand voltage 1.2/50	





	micro second wave		
27.7	Total creepage distance in air	mm	
27.8	Height of bushing above transformer	111111	
	tank		
28.0	Particulars of LV neutral bushing		
28.1	Make		
28.2	Туре		
28.3	Voltage rating		
28.4	Dry withstand voltage for one minute		
28.5	Wet withstand voltage for thirty		
00.0	minutes		
28.6	Total creepage distance in air, mm		
28.7	Height of bushing above transformer Tank, mm		
29.0	Time constant of transformer		
30.0	MCCB rating		
30.1	Make and model no.		
30.2	Utilization Category	Α	
30.3	Interrupting medium	Air	
30.4	Design	Molded case	
30.5	Type of operation	Independent manual	
30.3	Type of operation	closing	
30.6	Voltage rating	240/415	
30.0	Voltage rating	240/415	
	Number of poles		
30.8	Rated insulation voltage	1kV	
30.9	Rated impulse withstand voltage	8kV	
30.10	Rated frequency	50Hz	
30.11	Rated duty	Uninterrupted duty	
30.12	Ultimate Breaking Capacity Icu	35 KA min.	
30.13	Service Breaking capacity Ics	35 KA min.	
30.14	Trip current characteristics		
30.14.1	Rated current		
30.14.2	Overload setting	60% t0 100% of In.	
		Insteps of 10%	
30.14.3	Short circuit settings		
30.14.4	Trip time at rated uninterrupted current	>2.5 hrs	
30.14.5	Trip time at 2.5 Setting times normal	< 1 minute	
	current		
30.14.6	Trip time at 6 times normal current	< 5 secs.	
30	setting	3 3333.	
30.14.7	Trip time at 9 times normal current	40 millisec.	
30.17.7	setting	.5 111111000.	
31.0	HV fuse rating		
31.0	TIV IUSE TAILING		



31.1	Make	
31.2	Tripping curves provided	Yes/No
31.3	Fuse catalogue is provided	Yes/No
31.4	Tripping coordination graph of HV fuse and MCCB is provided	Yes/No
32.0	Transformer oil	
32.1	Dielectric strength	
32.2	Resistivity	
32.3	Acidity	
32.4	Tan delta	
32.5	Name of supplier	
32.6	Quantity of transformer oil, Liters	
33.0	Weight of the following	
33.1	Tank and fittings, Kgs	
33.2	Core, Kgs	
33.3	Winding weight, Kgs	
33.4	Core and windings, Kgs	
33.5	Transformer oil, Kgs	
33.6	Total weight of transformer including	
	oil, Kgs	
34.0	Overall dimensions of transformer	
34.1	Length	mm
34.2	Breadth	mm
34.3	Height	mm
35.0	Name of material and size used for	
	clamping of core winding	
35.1	Core clamp	
35.2	Tie rod	
35.3	Core bolt	
35.4	Bottom plate	
36.0	Tests	
36.1	Is the offered 16/25/50 kVA	
	distribution transformer type tested?	
	(Yes, No)	
36.2	All in process tests confirmed as per Cl. 9.1 (Yes/ No)	
36.3	All Routine Tests confirmed as per Cl.9.2 (Yes / No)	
36.4	All Type Tests confirmed as per Cl.9.3	
30.4	(Yes/ No)	
l	(100/140)	



20. Annexure – D Guaranteed Technical Particulars of Natural Ester oil

Bidder to submit duly filled & signed along with techno commercial offer.

Sr. No	Item description	Specification requirement Data by Vendor		
1.0	Manufacturer Name			
1.1	Address			
1.2	Contact person			
1.3	Contact telephone no			
2.0	Physical property			
2.1	Appearance	Clear, free from sediments and suspended matter.		
2.2	Viscosity			
2.2.1	At 100° C, Max	15 mm ² /sec		
2.2.2	At 40°, , Max	50 mm ² /sec		
2.3	Pour point , Max	-10° C		
2.4	Water content, Max	200 mg/kg (ppm)		
2.5	Density at 20° C, Max	1.0 g/ cm ³		
3.0	Electrical property			
3.1	Dielectric breakdown voltage(2.5 mm gap), Min	65kV		
3.2	Dielectric Dissipation factor (Tanδ) at 900 C, Max	0.05		
4.0	Chemical property			
4.1	Soluble acidity, Max	0.06 mg KOH/gm		
4.2	Corrosive sulfur	Non corrosive		
4.3	Total additives, Max	weight fraction 5%		
5.0	Performance-After oxidation stability test	-		
5.1	Total acidity, Max	0.6 mg KOH/g		
5.2	Viscosity at 400 C, Max	30% increase over the initial value		
5.3	Dielectric Dissipation factor (Tanδ) at 90° C, Max	0.5		
6.0	Health, safety and environment (HSE)			
6.1	Fire point, Min	300° C		
6.2	Flash point, Min	250° C		
6.3	Biodegradation	Readily biodegradable		
7.0	Packing & delivery as per specification	YES / NO		
7.1	Size of oil drum	210 liter minimum		
7.2	Quantity of oil to be supplied in DRUM			
8.0	Copy of Type test report	Submitted along with GTP?	YES / NO	
9.0	Deviation sheet	Submitted along with GTP? YES / NO		



TECHNICAL SPECIFICATION OF SINGLE PHASE OIL FILLED CSP TRANSFORMER

21. Annexure – E Recommended Spares (Data by Supplier)

List of recommended spares as following -

Sr No	Description of spare part	Unit	Quantity
1		No	
2		No	
3		No	
4		No	
5		No	
6		No	